

# On the inviscid limit of the system “viscous incompressible fluid + rigid body” with the Navier conditions

Gabriela Planas\*, Franck Sueur<sup>†‡</sup>

May 31, 2012

## Abstract

In this paper we consider the inviscid limit for the system “viscous incompressible fluid + rigid body” in  $\mathbb{R}^3$  when some Navier slip conditions are prescribed on the body’s boundary. We prove the convergence in the energy space of weak solutions “à la Leray” to smooth solutions of the system “inviscid incompressible fluid + rigid body” as the viscosity goes to zero. Moreover we show that the rate of convergence is optimal with respect to the viscosity and that the solid translation and rotation velocities converge in the Sobolev space  $H^1(0, T)$ , where  $T$  denotes the lifetime of the smooth solution of the inviscid system.

## 1 Introduction

Recently several efforts have been made to establish a Cauchy theory for various models involving a fluid and a immersed structure. In particular in the case where the structure is a rigid body and where the fluid is incompressible, there now exists a quite satisfactory range of results, at least in view of what is known in the case of a fluid alone; we may cite, among others, [25, 32, 22, 21, 33, 35, 42] for the case of inviscid fluid (we also refer to the introduction of [22] for a overview of these results) and [37, 14, 15, 8, 36] for the case of viscous fluid.

In this paper we deal with the issue of the inviscid limit for the system “viscous incompressible fluid + rigid body”, which involves an immersed rigid body moving into a viscous incompressible fluid driven by the Navier-Stokes equations.

Let us say here for sake of clarity that we will consider the case of a physical space of three dimensions and we will assume that the system occupies the whole of  $\mathbb{R}^3$  to avoid the extra difficulties which would be implied by an exterior boundary.

Formally dropping the viscosity in the equations of the system yields the system “inviscid incompressible fluid + rigid body”, which involves an immersed rigid body moving into a inviscid incompressible fluid driven by the Euler equations.

This paper aims at giving a justification of this formal procedure.

It is expected that the issue of justifying the inviscid limit is at least as difficult in the case of a moving body as in the case of a fixed body. Indeed the case of a fixed body can be seen as the limit case where the body’s inertia becomes infinite, cf. Sections 3.5 and 4.4.

This is quite a bad news since the inviscid limit is already quite intricate in the case of a fixed boundary, because of the boundary layers phenomenon. Moreover it is not clear a priori if it is possible to pass to the limit in the body’s dynamics, with such singular variations in the neighborhood.

These boundary layers issues are particularly involved in the case where one prescribes the no-slip condition on a fixed fluid-solid interface. In particular, it is not known at the time of writing if there is convergence in the

---

\*Departamento de Matemática, Instituto de Matemática, Estatística e Computação Científica, Universidade Estadual de Campinas, Rua Sergio Buarque de Holanda 651, 13083-859 Campinas, SP, Brasil

<sup>†</sup>CNRS, UMR 7598, Laboratoire Jacques-Louis Lions, F-75005, Paris, France

<sup>‡</sup>UPMC Univ Paris 06, UMR 7598, Laboratoire Jacques-Louis Lions, F-75005, Paris, France

energy space. A longstanding approach in this domain is Prandtl’s theory, but this theory fails to model flows with too small viscosity in general, see for instance [9, 2, 16, 23, 18, 24]. However a necessary and sufficient condition for the convergence to the Euler equations in the energy space has been given by Kato in [28]; it states that the energy dissipation rate of the viscous flows in a boundary strip of width proportional to the viscosity vanishes. Even if little is known about whether or not this condition is verified for a general given flow, this result gives a nice insight of the scale for which the description of the flow is necessary to understand the inviscid limit.

In the paper [38] the second author proved an extension of Kato’s result in the case of the system “viscous incompressible fluid + rigid body” with the no-slip condition on the fluid-solid interface: the convergence to the system “inviscid incompressible fluid + rigid body” holds true in the energy space if and only if the energy dissipation rate of the viscous flows in a boundary’s neighborhood of width proportional to the viscosity vanishes. As in the case of a fixed boundary it is not clear how to check this condition but this result seems to indicate that the issue of the inviscid limit in the case of a moving body is maybe not much harder than the one in the case of a fixed body.

In this paper we will prescribe some Navier conditions on the fluid-solid interface, which encode that the fluid slips with some friction on this boundary. In the case of a fixed boundary it is by now well understood that the issue of the inviscid limit is simplified compared to the no-slip conditions, at least when the friction coefficient is not too big; in particular the convergence holds true in the energy space (cf. for instance [1, 3, 7, 26, 27, 29, 34]). We prove here a similar result in the case of a moving body.

In fact we even prove a better convergence of the body’s dynamics (with respect to the fluid’s dynamics), i.e. a convergence in the Sobolev space  $H^1$ . This surprising result uses a new avatar of a well-known phenomenon in the theory of the systems involving an incompressible flow and a structure, namely the added mass phenomenon, for which we refer for instance to [6, 17].

The paper is organized as follows.

- In Section 2 we introduce the system “viscous incompressible fluid + rigid body” with Navier conditions.
- In Section 3 we establish the existence of an appropriate notion of weak solutions “à la Leray” of this system, after a change of variables. We will also establish a regularity property of the body’s dynamics and we will discuss the infinite inertia limit for this system.
- In Section 4 we recall a result of [38] which establishes the existence of smooth local-in-time solutions of the inviscid system and we also discuss the infinite inertia limit.
- In section 5 we state the main result of this paper about the convergence of the system “viscous incompressible fluid + rigid body” to the system “inviscid incompressible fluid + rigid body” as the viscosity goes to zero.
- Finally we give the proof of this result in Section 6.

## 2 The system “viscous incompressible fluid + rigid body” with Navier conditions

We consider a rigid body initially occupying a closed, bounded, connected and simply connected subset  $\mathcal{S}_0 \subset \mathbb{R}^3$  with smooth boundary. It rigidly moves so that at time  $t$  it occupies an isometric domain denoted by  $\mathcal{S}(t)$ . More precisely if we denote by  $h(t)$  the position of the center of mass of the body at time  $t$ , then there exists a rotation matrix  $Q(t) \in SO(3)$ , such that the position  $\eta(t, x) \in \mathcal{S}(t)$  at the time  $t$  of the point fixed to the body with an initial position  $x$  is

$$\eta(t, x) := h(t) + Q(t)(x - h(0)).$$

Of course this yields that  $Q(0) = \text{Id}_3$ .

Moreover since  $Q^T Q'(t)$  is skew symmetric there exists only one  $r(t)$  in  $\mathbb{R}^3$  such that for any  $x \in \mathbb{R}^3$ ,

$$Q^T Q'(t)x = r(t) \wedge x.$$

Accordingly, the solid velocity is given by

$$U_{\mathcal{S}}(t, x) := h'(t) + R(t) \wedge (x - h(t)) \text{ with } R(t) := Q(t)r(t).$$

Given a positive function  $\rho_{\mathcal{S}_0}$ , say in  $L^\infty(\mathcal{S}_0; \mathbb{R})$ , describing the density in the solid initially: the solid mass  $m > 0$ , the initial position  $h_0$  of the center of mass, and the initial value of the inertial matrix  $\mathcal{J}_0$  can be computed by its first moments:

$$m := \int_{\mathcal{S}_0} \rho_{\mathcal{S}_0}(x) dx > 0, \quad (1)$$

$$mh_0 := \int_{\mathcal{S}_0} x \rho_{\mathcal{S}_0}(x) dx, \quad (2)$$

$$\mathcal{J}_0 := \int_{\mathcal{S}_0} \rho_{\mathcal{S}_0}(x) (|x - h_0|^2 \text{Id}_3 - (x - h_0) \otimes (x - h_0)) dx. \quad (3)$$

At time  $t > 0$ , the density in the solid is given, for  $x \in \mathcal{S}(t)$ , by

$$\rho_{\mathcal{S}}(t, x) := \rho_{\mathcal{S}_0}(\eta(t, x)^{-1}(x)),$$

where  $\eta(t, x)^{-1}$  denotes the inverse at time  $t$  of the diffeomorphism  $x \mapsto \eta(t, x)$ ; so that, of course, the mass is preserved:

$$m = \int_{\mathcal{S}(t)} \rho_{\mathcal{S}}(t, x) dx.$$

Moreover, the position of the center of mass  $h(t)$  and the inertial matrix  $\mathcal{J}(t)$  are given by

$$mh(t) := \int_{\mathcal{S}(t)} x \rho_{\mathcal{S}}(t, x) dx,$$

$$\mathcal{J}(t) := \int_{\mathcal{S}(t)} \rho_{\mathcal{S}}(t, x) (|x - h(t)|^2 \text{Id}_3 - (x - h(t)) \otimes (x - h(t))) dx,$$

so that  $\mathcal{J}(t)$  is symmetric positive definite and satisfies Sylvester's law:

$$\mathcal{J}(t) = Q(t)\mathcal{J}_0Q^T(t).$$

Let us assume that in the rest of the space, that is, in the open set  $\mathcal{F}(t) := \mathbb{R}^3 \setminus \mathcal{S}(t)$ , there evolves a viscous incompressible fluid. We denote correspondingly  $\mathcal{F}_0 := \mathbb{R}^3 \setminus \mathcal{S}_0$  the initial fluid domain.

The complete system driving the dynamics reads

$$\frac{\partial U}{\partial t} + (U \cdot \nabla)U + \nabla P = \nu \Delta U \text{ for } x \in \mathcal{F}(t), \quad (4)$$

$$\text{div } U = 0 \text{ for } x \in \mathcal{F}(t), \quad (5)$$

$$U \cdot n = U_{\mathcal{S}} \cdot n \text{ for } x \in \partial \mathcal{S}(t), \quad (6)$$

$$(D(U)n) \wedge n = -\alpha(U - U_{\mathcal{S}}) \wedge n \text{ for } x \in \partial \mathcal{S}(t), \quad (7)$$

$$mh''(t) = - \int_{\partial \mathcal{S}(t)} \Sigma n ds, \quad (8)$$

$$(\mathcal{J}R)'(t) = - \int_{\partial \mathcal{S}(t)} (x - h(t)) \wedge \Sigma n ds, \quad (9)$$

$$U|_{t=0} = U_0, \quad (10)$$

$$h(0) = 0, \quad h'(0) = \ell_0, \quad R(0) = r_0. \quad (11)$$

Here  $U$  and  $P$  denote the fluid velocity and pressure, which are defined on  $\mathcal{F}(t)$  for each  $t$ , and  $\nu > 0$  is the fluid viscosity. The fluid is supposed to be homogeneous of density 1, to simplify the notations and without any loss of generality. The Cauchy stress tensor is defined by

$$\Sigma := -P \text{Id}_3 + 2\nu D(U),$$

where  $D(U)$  is the deformation tensor

$$D(U) := \left(\frac{1}{2}(\partial_j U_i + \partial_i U_j)\right)_{1 \leq i, j \leq 3}.$$

Above  $n$  denotes the unit outward normal on the boundary of the fluid domain,  $ds$  denotes the integration element on this boundary and  $\alpha \geq 0$  is a material constant (the friction coefficient).

Observe that, without loss of generality, we have assumed that  $h(0) = 0$  which means that the body is centered at the origin at the initial time  $t = 0$ .

In the sequel the integrals over open subsets of  $\mathbb{R}^3$  will always be taken with respect to the Lebesgue measure  $dx$  and the integrals over hypersurfaces of  $\mathbb{R}^3$  will always be taken with respect to the surface measure.

The equations (4)-(5) are the incompressible Navier-Stokes equations.

The equations (8) and (9) are the Newton's balance laws for linear and angular momenta: the fluid acts on the body through pressure forces.

The equations (6)-(7) are referred to as the Navier conditions and encode that the body's boundary is impermeable and that the fluid slips with some friction on this boundary.

This condition was introduced phenomenologically by Navier in 1823, cf. [31]. Let us mention some recent results about the derivation of such a condition, on the one hand from kinetic models (derivation from the Boltzmann equation with accommodation boundary conditions) see [10, 30, 1], and on the other hand from homogenization of rough boundaries [13, 19].

### 3 Weak solutions “à la Leray”

In this section we start by changing the variables in order to fix the fluid domain. It is fair to point out that this change of variable is here particularly simple as there is no exterior boundary. Then we establish the existence of an appropriate notion of weak solutions “à la Leray” of this system. We will observe that the solid velocity benefits from extra regularity with respect to what is expected from the energy estimate. We will also discuss the infinite inertia limit.

#### 3.1 A change of variables

In order to write the equations of the fluid in a fixed domain, we are going to use the following changes of variables:

$$\ell(t) := Q(t)^T h'(t), \quad u(t, x) := Q(t)^T U(t, Q(t)x + h(t)), \quad p(t, x) := P(t, Q(t)x + h(t)),$$

and we introduce

$$\sigma := -p \text{Id}_3 + 2\nu D(u), \quad \text{where } D(u) := \left(\frac{1}{2}(\partial_j u_i + \partial_i u_j)\right)_{i, j}.$$

Therefore the system (4)-(11) now reads

$$\frac{\partial u}{\partial t} + (u - u_S) \cdot \nabla u + r \wedge u + \nabla p = \nu \Delta u \quad \text{for } x \in \mathcal{F}_0, \quad (12)$$

$$\text{div } u = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (13)$$

$$u \cdot n = u_S \cdot n \quad \text{for } x \in \partial \mathcal{S}_0, \quad (14)$$

$$(D(u)n) \wedge n = -\alpha(u - u_S) \wedge n \quad \text{for } x \in \partial \mathcal{S}_0, \quad (15)$$

$$m\ell' = - \int_{\partial \mathcal{S}_0} \sigma n \, ds + m\ell \wedge r, \quad (16)$$

$$\mathcal{J}_0 r' = - \int_{\partial \mathcal{S}_0} x \wedge \sigma n \, ds + (\mathcal{J}_0 r) \wedge r, \quad (17)$$

$$u|_{t=0} = u_0, \quad (18)$$

$$h(0) = 0, \quad h'(0) = \ell_0, \quad r(0) = r_0, \quad (19)$$

with

$$u_S(t, x) := \ell(t) + r(t) \wedge x. \quad (20)$$

### 3.2 A weak formulation

With of the purpose of writing a weak formulation of the system (12)-(19) we introduce the following space

$$\mathcal{H} := \{\phi \in L^2(\mathbb{R}^3) / \operatorname{div} \phi = 0 \text{ in } \mathbb{R}^3 \text{ and } D(\phi) = 0 \text{ in } \mathcal{S}_0\}.$$

According to Lemma 1.1 in [39], p.18, for all  $\phi \in \mathcal{H}$ , there exist  $\ell_\phi \in \mathbb{R}^3$  and  $r_\phi \in \mathbb{R}^3$  such that for any  $x \in \mathcal{S}_0$ ,  $\phi(x) = \ell_\phi + r_\phi \wedge x$ . Therefore we extend the initial data  $u_0$  by setting  $u_0 := \ell_0 + r_0 \wedge x$  for  $x \in \mathcal{S}_0$ .

Conversely, when  $\phi \in \mathcal{H}$ , we denote  $\phi_S$  its restriction to  $\mathcal{S}_0$ .

Let us give here a result which will be useful in the sequel.

**Lemma 1.** *For any  $u, v \in \mathcal{H}$  with  $u|_{\mathcal{F}_0} \in H^2$  and  $v|_{\mathcal{F}_0} \in H^1$ ,*

$$\begin{aligned} \int_{\mathcal{F}_0} \Delta u \cdot v &= -2 \int_{\mathcal{F}_0} D(u) : D(v) + 2\ell_v \cdot \int_{\partial\mathcal{S}_0} D(u)n \, ds + 2r_v \cdot \int_{\partial\mathcal{S}_0} x \wedge D(u)n \, ds \\ &\quad + 2 \int_{\partial\mathcal{S}_0} \left( (D(u)n) \wedge n \right) \cdot \left( (v - v_S) \wedge n \right). \end{aligned}$$

*Proof.* We have

$$\int_{\mathcal{F}_0} \Delta u \cdot v = 2 \int_{\partial\mathcal{S}_0} (D(u)v) \cdot n - 2 \int_{\mathcal{F}_0} D(u) : D(v) = 2 \int_{\partial\mathcal{S}_0} (D(u)n) \cdot v - 2 \int_{\mathcal{F}_0} D(u) : D(v),$$

since  $D(u)$  is symmetric. Moreover

$$\int_{\partial\mathcal{S}_0} (D(u)n) \cdot v = \int_{\partial\mathcal{S}_0} \left( (D(u)n) \cdot n \right) (v \cdot n) + \int_{\partial\mathcal{S}_0} \left( (D(u)n) \wedge n \right) \cdot (v \wedge n).$$

But

$$\begin{aligned} \int_{\partial\mathcal{S}_0} \left( (D(u)n) \cdot n \right) (v \cdot n) &= \int_{\partial\mathcal{S}_0} \left( (D(u)n) \cdot n \right) (v_S \cdot n) \\ &= \int_{\partial\mathcal{S}_0} \left( ((D(u)n) \cdot n)n \right) \cdot v_S \\ &= \int_{\partial\mathcal{S}_0} \left( D(u)n - (D(u)n)_{tan} \right) \cdot v_S \\ &= \ell_v \cdot \int_{\partial\mathcal{S}_0} D(u)n \, ds + r_v \cdot \int_{\partial\mathcal{S}_0} x \wedge D(u)n \, ds - \int_{\partial\mathcal{S}_0} (D(u)n)_{tan} \cdot v_S \\ &= \ell_v \cdot \int_{\partial\mathcal{S}_0} D(u)n \, ds + r_v \cdot \int_{\partial\mathcal{S}_0} x \wedge D(u)n \, ds - \int_{\partial\mathcal{S}_0} \left( D(u)n \wedge n \right) \cdot (v_S \wedge n). \end{aligned}$$

Gathering the previous identities yields the result. □

Now we endow the space  $L^2(\mathbb{R}^3)$  with the following inner product, which is equivalent to the usual one,

$$(\phi, \psi)_{\mathcal{H}} := \int_{\mathcal{F}_0} \phi \cdot \psi \, dx + \int_{\mathcal{S}_0} \rho_{\mathcal{S}_0} \phi \cdot \psi \, dx.$$

When  $\phi, \psi$  are in  $\mathcal{H}$  we obtain:

$$(\phi, \psi)_{\mathcal{H}} = \int_{\mathcal{F}_0} \phi \cdot \psi \, dx + m\ell_\phi \cdot \ell_\psi + \mathcal{J}_0 r_\phi \cdot r_\psi, \tag{21}$$

by using (1)-(2)-(3). The spaces  $L^2(\mathbb{R}^3)$  and  $\mathcal{H}$  are clearly Hilbert spaces for the scalar product  $(\cdot, \cdot)_{\mathcal{H}}$ .

**Proposition 1.** *A smooth solution of (12)-(19) satisfies the following: for any  $v \in C^\infty([0, T]; \mathcal{H})$  such that  $v|_{\overline{\mathcal{F}_0}} \in C^\infty([0, T]; C_c^\infty(\overline{\mathcal{F}_0}))$ , for all  $t \in [0, T]$ ,*

$$(u, v)_{\mathcal{H}}(t) - (u_0, v|_{t=0})_{\mathcal{H}} = \int_0^t \left[ (u, \partial_t v)_{\mathcal{H}} + 2\nu a(u, v) + b(u, u, v) \right], \quad (22)$$

where

$$\begin{aligned} a(u, v) &:= -\alpha \int_{\partial \mathcal{S}_0} (u - u_{\mathcal{S}}) \cdot (v - v_{\mathcal{S}}) - \int_{\mathcal{F}_0} D(u) : D(v) \\ b(u, v, w) &:= m \det(r_u, \ell_v, \ell_w) + \det(\mathcal{J}_0 r_u, r_v, r_w) + \int_{\mathcal{F}_0} \left( [(u - u_{\mathcal{S}}) \cdot \nabla w] \cdot v - \det(r_u, v, w) \right). \end{aligned}$$

In the sequel we will consider several asymptotics with respect to the parameters  $\alpha, \nu, m$  and  $\mathcal{J}_0$ . Let us therefore stress here that the forms  $a$  and  $b$  above depend respectively on  $\alpha, \mathcal{S}_0$  and on  $m, \mathcal{J}_0, \mathcal{S}_0$ .

*Proof.* Let  $u$  be a smooth solution of (12)-(19) on  $[0, T]$  and  $v \in C^\infty([0, T]; \mathcal{H})$  such that  $v|_{\overline{\mathcal{F}_0}} \in C^\infty([0, T]; C_c^\infty(\overline{\mathcal{F}_0}))$ . We first observe that the result of Proposition 1 will follow, by an integration by parts in time, from the following claim: for any  $t \in [0, T]$ ,

$$(\partial_t u, v)_{\mathcal{H}} = 2\nu a(u, v) + b(u, u, v). \quad (23)$$

To prove the claim, we multiply equation (12) by  $v$  and integrate over  $\mathcal{F}_0$ :

$$\int_{\mathcal{F}_0} \frac{\partial u}{\partial t} \cdot v + \int_{\mathcal{F}_0} [((u - u_{\mathcal{S}}) \cdot \nabla) u] \cdot v + \int_{\mathcal{F}_0} (r(t) \wedge u) \cdot v + \int_{\mathcal{F}_0} \nabla p \cdot v = \int_{\mathcal{F}_0} \nu \Delta u \cdot v.$$

We then use some integrations by parts, taking into account (13) and (14), to get

$$\begin{aligned} \int_{\mathcal{F}_0} [((u - u_{\mathcal{S}}) \cdot \nabla) u] \cdot v &= - \int_{\mathcal{F}_0} u \cdot ((u - u_{\mathcal{S}}) \cdot \nabla v), \\ \int_{\mathcal{F}_0} (r(t) \wedge u) \cdot v &= \int_{\mathcal{F}_0} \det(r, u, v), \\ \int_{\mathcal{F}_0} \nabla p \cdot v &= \int_{\partial \mathcal{S}_0} pn \cdot v. \end{aligned}$$

Next, we observe that

$$\int_{\partial \mathcal{S}_0} pn \cdot v = \ell_v \cdot \int_{\partial \mathcal{S}_0} pn \, ds + r_v \cdot \int_{\partial \mathcal{S}_0} x \wedge pn \, ds.$$

Therefore, using Lemma 1, the Navier conditions and (16)-(17), we obtain

$$\begin{aligned} \int_{\partial \mathcal{S}_0} pn \cdot v - \int_{\mathcal{F}_0} \nu \Delta u \cdot v &= -\ell_v \cdot \int_{\partial \mathcal{S}_0} \sigma n \, ds - r_v \cdot \int_{\partial \mathcal{S}_0} x \wedge \sigma n \, ds \\ &\quad + 2\alpha \nu \int_{\partial \mathcal{S}_0} (u - u_{\mathcal{S}}) \cdot (v - v_{\mathcal{S}}) + 2\nu \int_{\mathcal{F}_0} D(u) : D(v) \\ &= m \ell_v \cdot \ell' + \mathcal{J}_0 r_v \cdot r' - \det(m \ell, r, \ell_v) - \det(\mathcal{J}_0 r, r, r_v) \\ &\quad + 2\alpha \nu \int_{\partial \mathcal{S}_0} (u - u_{\mathcal{S}}) \cdot (v - v_{\mathcal{S}}) + 2\nu \int_{\mathcal{F}_0} D(u) : D(v). \end{aligned}$$

Gathering all these equalities yields (23). □

We introduce now the concept of weak solutions “à la Leray”.

**Definition 1.** *We say that*

$$u \in C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \mathcal{V})$$

*is a weak solution of the system (12)-(19) if for all  $v \in C^\infty([0, T]; \mathcal{H})$  such that  $v|_{\overline{\mathcal{F}_0}} \in C^\infty([0, T]; C_c^\infty(\overline{\mathcal{F}_0}))$  and for all  $t \in [0, T]$ , (22) holds true.*

Let us remark that a standard density argument allows us to take less smooth test vector fields  $v$  in the above weak formulation. More precisely, to enlarge the space of the test functions, we introduce the spaces

$$\underline{\mathcal{V}} := \{\phi \in \mathcal{H} / \int_{\mathcal{F}_0} |\nabla\phi(y)|^2 dy < +\infty\} \text{ and } \mathcal{V} := \{\phi \in \mathcal{H} / \int_{\mathcal{F}_0} |\nabla\phi(y)|^2 (1 + |y|^2) dy < +\infty\},$$

respectively endowed with the norms

$$\|\phi\|_{\underline{\mathcal{V}}} := \|\phi\|_{\mathcal{H}} + \|\nabla\phi\|_{L^2(\mathcal{F}_0, dy)} \text{ and } \|\phi\|_{\mathcal{V}} := \|\phi\|_{\mathcal{H}} + \|\nabla\phi\|_{L^2(\mathcal{F}_0, (1+|y|^2)^{\frac{1}{2}} dy)}.$$

It is worth to notice from now on that  $b$  is a trilinear continuous form on  $\underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \mathcal{V}$ : there exists a constant  $C > 0$  such that for any  $(u, v, w) \in \underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \mathcal{V}$ ,

$$|b(u, v, w)| \leq C \|u\|_{\underline{\mathcal{V}}} \|v\|_{\underline{\mathcal{V}}} \|w\|_{\mathcal{V}}. \quad (24)$$

This follows easily from Holder's inequality and the following interpolation inequality

$$\|v\|_{L^4(\mathcal{F}_0)} \leq \sqrt{2} \|v\|_{L^2(\mathcal{F}_0)}^{\frac{1}{4}} \|\nabla v\|_{L^2(\mathcal{F}_0)}^{\frac{3}{4}}. \quad (25)$$

Observe in particular that the weight in the definition of  $\mathcal{V}$  allows to handle the rotation part of  $u_S$ .

Moreover the trilinear form  $b$  satisfies the following crucial property

$$(u, v) \in \underline{\mathcal{V}} \times \mathcal{V} \text{ implies } b(u, v, v) = 0. \quad (26)$$

On the other hand, for any  $u, v$  in  $\underline{\mathcal{V}}$ ,

$$|a(u, v)| \leq C \|u\|_{\underline{\mathcal{V}}} \|v\|_{\underline{\mathcal{V}}}. \quad (27)$$

In fact, to deal with the boundary integral, we introduce a smooth cut-off function  $\chi$  defined on  $\overline{\mathcal{F}_0}$  such that  $\chi = 1$  in  $\Gamma_c$  and  $\chi = 0$  in  $\mathcal{F}_0 \setminus \Gamma_{2c}$ , where

$$\Gamma_c := \{x \in \mathcal{F}_0 / d(x) < c\} \text{ with } d(x) := \text{dist}(x, \partial\mathcal{S}_0).$$

Let us denote

$$\psi_S^u(t, x) := \frac{1}{2}(\ell_u(t) \wedge x - r_u(t)|x|^2) \text{ and } \tilde{u}_S := \text{curl}(\chi\psi_S^u),$$

and let us define similarly  $\tilde{v}_S$ .

Thus,  $\tilde{u}_S$  and  $\tilde{v}_S$  are equal respectively, to  $u_S$  and  $v_S$  near  $\partial\mathcal{S}_0$ , vanish away  $\mathcal{S}_0$ , and are divergence free. Moreover,  $\|\tilde{u}_S\|_{H^1(\mathcal{F}_0)} \leq C(\|\ell_u\| + \|r_u\|)$ , and a similar estimate holds for  $\tilde{v}_S$ . Then, we apply the Hölder inequality and the trace theorem, to arrive at

$$\begin{aligned} \left| \int_{\partial\mathcal{S}_0} (u - u_S) \cdot (v - v_S) \right| &= \left| \int_{\partial\mathcal{S}_0} (u - \tilde{u}_S) \cdot (v - \tilde{v}_S) \right| \\ &\leq C \|u - \tilde{u}_S\|_{H^1(\mathcal{F}_0)} \|v - \tilde{v}_S\|_{H^1(\mathcal{F}_0)} \\ &\leq C(\|u\|_{H^1(\mathcal{F}_0)} + \|\ell_u\| + \|r_u\|)(\|v\|_{H^1(\mathcal{F}_0)} + \|\ell_v\| + \|r_v\|), \end{aligned}$$

so that, (27) follows.

These previous arguments allows us to take less smooth test vector fields  $v$  in the weak formulation (22), for instance, belonging to  $H^1(0, T; \mathcal{H}) \cap L^4(0, T; \mathcal{V})$ .

### 3.3 An extension of Leray's theorem

The following result establishes the existence of global weak solutions of the system (12)-(19).

**Theorem 1.** *Let be given  $u_0 \in \mathcal{H}$  and  $T > 0$ . Then there exists a weak solution  $u$  of (12)-(19) in  $C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \underline{\mathcal{V}})$ . Moreover this solution satisfies the following energy inequality: for almost any  $t \in [0, T]$ ,*

$$\frac{1}{2} \|u(t, \cdot)\|_{\mathcal{H}}^2 + 2\nu \int_{(0, t) \times \mathcal{F}_0} |D(u)|^2 + 2\alpha\nu \int_0^t \int_{\partial\mathcal{S}_0} |u - u_S|^2 \leq \frac{1}{2} \|u_0\|_{\mathcal{H}}^2. \quad (28)$$

Theorem 1 is the counterpart of Theorem 4.5 of [37] for the Navier conditions instead of the no-slip conditions.

*Proof.* We will proceed in several steps. In particular because the space of test functions  $\mathcal{V}$  involves a weight which makes it smaller than the space  $\underline{\mathcal{V}}$  involved by the energy estimates, we will first introduce a truncation of the solid velocity far from the solid. This strategy was already used in [33] in a slightly different context.

**Truncation.** Let  $R_0 > 0$  be such that  $\mathcal{S}_0 \subset B(0, \frac{R_0}{2})$ . For  $R > R_0$ , let  $\chi_R : \mathbb{R}^3 \rightarrow \mathbb{R}^3$  be a smooth vector field such that  $r \wedge \chi_R$  is divergence free,  $\chi_R(x) = x$  for  $x \in B(0, R)$  and satisfying  $\|\chi_R\|_{L^\infty(\mathbb{R}^3; \mathbb{R}^3)} \leq R$ . Indeed one may define for example  $\chi_R$  by the formula  $\chi_R(x) = \frac{R}{|x|}x$  for  $x \in \mathbb{R}^3 \setminus B(0, R)$ .

Observe in particular that for any  $r \in \mathbb{R}^3$ , for any  $w \in \mathcal{V}$ ,

$$(r \wedge \chi_R) \cdot \nabla w \rightarrow (r \wedge x) \cdot \nabla w \text{ in } L^2(\mathbb{R}^3), \text{ when } R \rightarrow +\infty, \quad (29)$$

by Lebesgue's dominated convergence theorem.

Then we truncate the solid velocity  $u_S$  defined in (20) by  $u_{S,R}(t, x) := \ell(t) + r(t) \wedge \chi_R(x)$ , and we introduce the form

$$b_R(u, v, w) := m \det(r_u, \ell_v, \ell_w) + \det(\mathcal{J}_0 r_u, r_v, r_w) + \int_{\mathcal{F}_0} \left( [(u - u_{S,R}) \cdot \nabla w] \cdot v - \det(r_u, v, w) \right).$$

The interest of such a truncation  $b_R$  of  $b$  is that it is now well-defined and trilinear on  $\underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \underline{\mathcal{V}}$  (note that the third argument is here taken not only in  $\mathcal{V}$  but in the larger space  $\underline{\mathcal{V}}$ ) and continuous in the sense that there exists a constant  $C > 0$  such that for any  $(u, v, w) \in \underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \underline{\mathcal{V}}$ ,

$$|b_R(u, v, w)| \leq C \|u\|_{\underline{\mathcal{V}}} \|v\|_{\underline{\mathcal{V}}} \|w\|_{\underline{\mathcal{V}}}. \quad (30)$$

Of course the constant  $C$  in (30) depends on  $R$ . However, when restricting  $b_R$  to  $\underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \mathcal{V}$ , there exists  $C > 0$  such that for any  $R > R_0$ , for any  $(u, v, w) \in \underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \mathcal{V}$ ,

$$|b_R(u, v, w)| \leq C \|u\|_{\underline{\mathcal{V}}} \|v\|_{\underline{\mathcal{V}}} \|w\|_{\mathcal{V}}. \quad (31)$$

We also have that there exists  $C > 0$  such that for any  $R > R_0$ , for any  $(u, v) \in \underline{\mathcal{V}} \times \mathcal{V}$ ,

$$|b_R(u, u, v)| \leq C (\|u\|_{L^4(\mathcal{F}_0)}^2 + \|u\|_{\mathcal{H}}^2) \|v\|_{\mathcal{V}}. \quad (32)$$

Actually, estimates (31) and (32) are proved by proceeding in the same way than for the proof of (24).

Moreover the cancellation property (26) is still correct:

$$(u, v) \in \underline{\mathcal{V}} \times \underline{\mathcal{V}} \text{ implies } b_R(u, v, v) = 0. \quad (33)$$

Finally we deduce from (29) that for any  $(u, v, w) \in \underline{\mathcal{V}} \times \underline{\mathcal{V}} \times \mathcal{V}$ ,

$$b_R(u, v, w) \rightarrow b(u, v, w) \text{ when } R \rightarrow +\infty. \quad (34)$$

**Existence for the truncated system.** Then, given  $u_0 \in \mathcal{H}$  and  $T > 0$ , there exists  $u_R$  in  $C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \underline{\mathcal{V}})$  satisfying, for any  $v \in C^\infty([0, T]; \mathcal{H})$  such that  $v|_{\overline{\mathcal{F}_0}} \in C^\infty([0, T]; C_c^\infty(\overline{\mathcal{F}_0}))$ , and for all  $t \in [0, T]$ ,

$$(u_R, v)_{\mathcal{H}}(t) - (u_0, v|_{t=0})_{\mathcal{H}} = \int_0^t \left[ (u_R, \partial_t v)_{\mathcal{H}} + 2\nu a(u_R, v) + b_R(u_R, u_R, v) \right]. \quad (35)$$

Moreover  $u_R$  verifies for almost any  $t \in [0, T]$  the energy inequality (28).

This can be proved with very standard methods, by example considering some Faedo-Galerkin approximations and passing to the limit. Let us therefore sketch a proof of it referring for example to [40] where a comprehensive study of the Leray theorem for the classical case of a fixed boundary is treated.

Let  $(w_j)_{j \geq 1}$  be a Hilbert basis of  $\underline{\mathcal{V}}$ . For simplicity, since the set

$$\mathcal{Y} := \{ \phi \in C_c^\infty(\mathbb{R}^3) / \operatorname{div} \phi = 0 \text{ in } \mathbb{R}^3 \text{ and } D(\phi) = 0 \text{ in } \mathcal{S}_0 \}$$

is dense in  $\underline{\mathcal{Y}}$ , we take  $w_j \in \mathcal{Y}$ , for all  $j \geq 1$ .

We define an approximate solution  $u_N := u_{N,R}$  (in the sequel we will omit the dependence on  $R$  for the sake of clarity) of the form  $u_N = \sum_{i=1}^N g_{iN}(t)w_i$  satisfying, for any  $j = 1, \dots, N$ ,

$$(\partial_t u_N, w_j)_{\mathcal{H}} = 2\nu a(u_N, w_j) + b_R(u_N, u_N, w_j), \quad (36)$$

$$u_N|_{t=0} = u_{N0}, \quad (37)$$

where  $u_{N0}$  is the orthogonal projection in  $\mathcal{H}$  of  $u_0$  onto the space spanned by  $w_1, \dots, w_N$ . Let us explain why such  $(u_N)_N$  do exist. First we introduce the matrices:

$$\mathcal{M}_N := [(w_i, w_j)_{\mathcal{H}}]_{1 \leq i, j \leq N}, \quad \mathcal{G}_N := [g_{1N} \ \dots \ g_{NN}], \quad \mathcal{A}_N := [a(w_i, w_j)]_{1 \leq i, j \leq N},$$

and for any  $u, v \in \mathbb{R}^N$ ,  $\mathcal{B}_N(u, v) := (\mathcal{B}_{Nj}(u, v))_{1 \leq j \leq N}$ , where  $\mathcal{B}_{Nj}(u, v) := \sum_{1 \leq i, k \leq N} u_i v_k b_R(w_i, w_k, w_j)$ . Then the equation (36) can be recast as the following nonlinear differential system for the functions  $(g_{iN})_{1 \leq i \leq N}$ :

$$\mathcal{G}'_N(t) = \mathcal{M}_N^{-1} \left( 2\nu \mathcal{A}_N \mathcal{G}_N + \mathcal{B}_N(\mathcal{G}_N, \mathcal{G}_N) \right)$$

and the initial condition (37) is equivalent to an initial condition of the form  $\mathcal{G}_N(0) = \mathcal{G}_{N,0}$ . According to the Cauchy-Lipschitz theorem this system has a maximal solution defined on some time interval  $[0, T_N]$  with  $T_N > 0$ . Moreover if  $T_N < T$  then  $\|u_N\|_{\mathcal{H}}$  must tend to  $+\infty$  as  $t \rightarrow T_N$ .

The following energy estimate shows that this does not happen and therefore  $T_N = T$ . For any  $j = 1, \dots, N$ , we multiply (36) by  $g_{jN}(t)$  and we sum the resulting identities to obtain, thanks to (33),  $\frac{1}{2} \partial_t \|u_N\|_{\mathcal{H}}^2 = 2\nu a(u_N, u_N)$ , so that, by integration in time, we have

$$\frac{1}{2} \|u_N(t, \cdot)\|_{\mathcal{H}}^2 + 2\nu \int_{(0,t) \times \mathbb{R}^3} |D(u_N)|^2 + 2\alpha\nu \int_0^t \int_{\partial S_0} |u_N - u_{N,S}|^2 \leq \frac{1}{2} \|u_{N0}\|_{\mathcal{H}}^2 \leq \frac{1}{2} \|u_0\|_{\mathcal{H}}^2. \quad (38)$$

In particular, the sequence  $(u_N)_N$  is bounded in  $L^\infty(0, T; \mathcal{H}) \cap L^2(0, T; \underline{\mathcal{Y}})$ . Therefore, there exists a subsequence of  $(u_N)_N$ , relabelled the same, converging weakly-\* in  $L^\infty(0, T; \mathcal{H})$  and weakly in  $L^2(0, T; \underline{\mathcal{Y}})$  to  $u \in L^\infty(0, T; \mathcal{H}) \cap L^2(0, T; \underline{\mathcal{Y}})$ , as  $N \rightarrow +\infty$ , which satisfies, for almost any  $t \in [0, T]$ , the energy inequality (28).

In order to pass to the limit in the nonlinear term in (36), we need a strong convergence. We will closely follow the classical arguments in Ch. 3 of [40]. To this end, we are going to bound a fractional derivative in time of the functions  $u_N$  by applying the Fourier transform. We therefore first extend the functions  $u_N$  to the whole time line as follows. For any  $N > 1$  let us now denote by  $\tilde{u}_N$  the function defined from  $\mathbb{R}$  to  $\mathcal{H}$  which is equal to  $u_N$  on  $[0, T]$  and by 0 outside. We denote by  $\hat{u}_N$  the Fourier transform of  $\tilde{u}_N$ , defined by  $\hat{u}_N(\tau) := \int_{\mathbb{R}} e^{-2i\pi t\tau} \tilde{u}_N(t) dt$ . Similarly we extend the functions  $g_{iN}$  by 0 outside  $[0, T]$  and we denote by  $\hat{g}_{iN}$  their respective Fourier transform.

According to Th. 2.2 in [40] it is sufficient to prove that there exists  $\gamma > 0$  such that  $(|\tau|^\gamma \hat{u}_N(\tau))_N$  is bounded in  $L^2(\mathbb{R}; \mathcal{H})$  to deduce that the sequence  $(u_N)_N$  is relatively compact in  $L^2(0, T; L^2_{loc}(\mathbb{R}^3))$ .

Let us denote, for  $t \in \mathbb{R}$ , by  $\tilde{f}_N(t)$  the linear form on  $\underline{\mathcal{Y}}$  defined by

$$\langle \tilde{f}_N(t), w \rangle := 2\nu a(u_N(t), w) + b_R(u_N(t), u_N(t), w) \text{ for } t \in [0, T] \text{ and } \tilde{f}_N(t) := 0 \text{ otherwise,}$$

so that the equation (36) becomes

$$(\partial_t \tilde{u}_N, w_j)_{\mathcal{H}} = -(u_{N0}, w_j)_{\mathcal{H}} \delta_0(t) + (u_N|_{t=T}, w_j)_{\mathcal{H}} \delta_T(t) + \langle \tilde{f}_N, w_j \rangle, \quad (39)$$

and then, taking the Fourier transform in time, we get for any  $\tau \in \mathbb{R}$ ,

$$2\pi i\tau (\hat{u}_N, w_j)_{\mathcal{H}} = -(u_{N0}, w_j)_{\mathcal{H}} + (u_N|_{t=T}, w_j)_{\mathcal{H}} e^{-2i\pi T\tau} + \langle \hat{f}_N, w_j \rangle.$$

This yields, multiplying by  $\hat{g}_{jN}$  and summing over  $1 \leq j \leq N$ , that, for any  $\tau \in \mathbb{R}$ ,

$$2\pi i\tau \|\hat{u}_N(\tau)\|_{\mathcal{H}}^2 = -(u_{N0}, \hat{u}_N)_{\mathcal{H}} + (u_N|_{t=T}, \hat{u}_N)_{\mathcal{H}} e^{-2i\pi T\tau} + \langle \hat{f}_N, \hat{u}_N \rangle.$$

Thanks to (27) and (30), there exists  $C > 0$  such that for any  $t \in [0, T]$ ,  $\|f_N(t)\|_{\underline{\mathcal{Y}'}} \leq C(\|u_N(t)\|_{\underline{\mathcal{Y}}} + \|u_N(t)\|_{\underline{\mathcal{Y}}})$ . Moreover, for any  $\tau \in \mathbb{R}$ ,  $\|\hat{f}_N(\tau)\|_{\underline{\mathcal{Y}'}} \leq \int_0^T \|f_N(t)\|_{\underline{\mathcal{Y}'}} dt$ . Thus,  $(\sup_{\tau \in \mathbb{R}} \|\hat{f}_N(\tau)\|_{\underline{\mathcal{Y}'}})$  is bounded, and the initial and

final values  $u_{N0}$  and  $u_N|_{t=T}$  are bounded as well. Therefore there exists  $C > 0$  such that  $\tau \|\hat{u}_N(\tau)\|_{\mathcal{H}}^2 \leq C \|\hat{u}_N(\tau)\|_{\mathcal{V}}$ . Now, we observe that there exists  $C > 0$  such that for any  $\tau \in \mathbb{R}$ ,  $|\tau|^{\frac{1}{4}} \leq C(1 + |\tau|)(1 + |\tau|)^{-\frac{3}{4}}$ , to deduce that

$$\begin{aligned} \int_{\mathbb{R}} |\tau|^{\frac{1}{4}} \|\hat{u}_N(\tau)\|_{\mathcal{H}}^2 d\tau &\leq C \int_{\mathbb{R}} \frac{1 + |\tau|}{1 + |\tau|^{\frac{3}{4}}} \|\hat{u}_N(\tau)\|_{\mathcal{H}}^2 d\tau \\ &\leq C \int_{\mathbb{R}} \frac{1}{1 + |\tau|^{\frac{3}{4}}} \|\hat{u}_N(\tau)\|_{\mathcal{V}} d\tau + C \int_{\mathbb{R}} \|\hat{u}_N(\tau)\|_{\mathcal{V}}^2 d\tau \\ &\leq C \int_{\mathbb{R}} \|\hat{u}_N(\tau)\|_{\mathcal{V}}^2 d\tau, \end{aligned}$$

by the Cauchy-Schwarz inequality. Then it follows from the Parseval identity that  $(|\tau|^{\frac{1}{8}} \hat{u}_N(\tau))_N$  is bounded in  $L^2(\mathbb{R}; \mathcal{H})$ .

Then, we can classically pass to the limit in (36) as  $N \rightarrow \infty$ , and obtain that (35) is satisfied.

**Endgame.** Since the bounds given by the energy estimate (28) are uniform with respect to  $R > R_0$ , there exists a subsequence  $(u_{R_k})_k$  converging to  $u \in C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \mathcal{V})$  for the weak (or weak-\*) topologies, satisfying (28) for almost any  $t \in [0, T]$ . This allows to pass to the limit in all the terms involved in (35) except for the trilinear term.

On the other hand it is sufficient to prove for any  $v \in C^\infty([0, T]; \mathcal{H})$  such that  $v|_{(0, T) \times \overline{\mathcal{F}_0}} \in C_c^\infty((0, T) \times \overline{\mathcal{F}_0})$

$$0 = \int_0^t \left[ (u, \partial_t v)_{\mathcal{H}} + 2\nu a(u, v) + b(u, u, v) \right], \quad (40)$$

to deduce, by standard arguments, that  $u$  is a weak solution of (12)-(19).

It therefore only remains to prove that there exists a subsequence, still denoted  $(u_{R_k})_k$ , such that for any  $v \in C^\infty([0, T]; \mathcal{H})$  with  $v|_{(0, T) \times \overline{\mathcal{F}_0}} \in C_c^\infty((0, T) \times \overline{\mathcal{F}_0})$ , as  $k \rightarrow \infty$ ,

$$\int_0^t b_{R_k}(u_{R_k}, u_{R_k}, v) \rightarrow \int_0^t b(u, u, v). \quad (41)$$

First let us observe that to prove (41) it will be enough to show that the sequence  $(u_{R_k})_k$  is relatively compact in  $L^2(0, T; L^2_{loc}(\mathbb{R}^3))$ . Indeed this yields that there exists a subsequence, still denoted  $(u_{R_k})_k$ , converging to  $u$  in  $L^2(0, T; L^2_{loc}(\mathbb{R}^3))$ , and then we use the decomposition

$$b_{R_k}(u_{R_k}, u_{R_k}, v) - b(u, u, v) = b_{R_k}(u, u, v) - b(u, u, v) + b_{R_k}(u_{R_k} - u, u_{R_k}, v) - b_{R_k}(u, u - u_{R_k}, v).$$

Observe that we can bound

$$|b_{R_k}(u, \bar{u}, v)| \leq C \|u\|_K \|u\|_{\mathcal{H}_K} \|\bar{u}\|_K \|v\|_{Lip(K)},$$

where  $C$  is independent of  $R_k$ , the set  $K$  is such that  $\text{supp } v \subset K$  and  $\|\cdot\|_{\mathcal{H}_K}$  is defined by

$$\|\phi\|_{\mathcal{H}_K}^2 := \int_{\mathcal{F}_0 \cap K} |\phi|^2 dx + \int_{S_0 \cap K} \rho_{S_0} |\phi|^2 dx.$$

Hence, (41) follows from the local strong convergence and (34).

Now, with the purpose of proving that  $(u_{R_k})_k$  is relatively compact in  $L^2(0, T; L^2_{loc}(\mathbb{R}^3))$ , we are going to show that  $(\partial_t u_{R_k})_k$  is bounded in  $L^{\frac{4}{3}}(0, T; \mathcal{V}')$ . Then the Aubin-Lions lemma will entail the desired compactness.

The bound of  $(\partial_t u_{R_k})_k$  is obtained as follows. We first combine the interpolation inequality (25) with the energy bounds, to see that  $(u_{R_k})_k$  is bounded in  $L^{\frac{8}{3}}(0, T; L^4(\mathcal{F}_0))$ .

Next we use (32) and Holder's inequality to get that there exists  $C > 0$  such that for any  $k \in \mathbb{N}$ , for any  $v \in L^4(0, T; \mathcal{V})$ ,

$$\left| \int_0^t b_{R_k}(u_{R_k}, u_{R_k}, v) \right| \leq C \|v\|_{L^4(0, T; \mathcal{V})}.$$

Then we easily infer from (35) the desired estimate of  $(\partial_t u_{R_k})_k$ , and therefore the proof of Theorem 1 is complete.  $\square$

### 3.4 A regularity property

In the present case of the Navier conditions, the dynamics of the body benefits from a remarkable regularity property stated in the proposition below. We will make use a slight variant of (24), which involves the space

$$\widehat{\mathcal{V}} := \{\phi \in \mathcal{V} / \phi|_{\mathcal{F}_0} \in \text{Lip}(\overline{\mathcal{F}_0})\}, \text{ endowed with the norm } \|\phi\|_{\widehat{\mathcal{V}}} := \|\phi\|_{\mathcal{V}} + \|\phi\|_{\text{Lip}(\overline{\mathcal{F}_0})}.$$

Then one may extend  $b$  to  $\mathcal{H} \times \mathcal{H} \times \widehat{\mathcal{V}}$  such that there exists a constant  $C > 0$  such that for any  $(u, v, w) \in \mathcal{H} \times \mathcal{H} \times \widehat{\mathcal{V}}$ ,

$$|b(u, v, w)| \leq C \|u\|_{\mathcal{H}} \|v\|_{\mathcal{H}} \|w\|_{\widehat{\mathcal{V}}}. \quad (42)$$

Let us emphasize for the comfort of the reader that  $\widehat{\mathcal{V}} \subset \mathcal{V} \subset \mathcal{V}$ .

Let us also denote by  $\lambda_i$ ,  $i = 1, 2, 3$  the eigenvalues of the inertial matrix  $\mathcal{J}_0$ , which is symmetric definite positive, so that,  $\lambda_i > 0$  for all  $i = 1, 2, 3$ . Moreover, we consider the spectral norms  $\|\mathcal{J}_0\| := \max(\lambda_i)$  and  $\|\mathcal{J}_0^{-1}\|^{-1} := \min(\lambda_i)$ .

**Proposition 2.** *Let be given  $u_0 \in \mathcal{H}$  and  $T > 0$ . Consider a weak solution  $u$  of (12)-(19) given by Theorem 1. Then  $\ell$  and  $r$  are in  $H^1(0, T; \mathbb{R}^3)$  and satisfy the following: there exist*

1. a  $6 \times 6$  definite positive symmetric matrix  $\mathcal{M}$  depending only on  $\mathcal{S}_0$ ,  $m$  and  $\mathcal{J}_0$  such that there exist  $\underline{m} > 0$  and  $\beta > 0$  depending only on  $\mathcal{S}_0$  such that, for any  $F$  and  $T$  in  $\mathbb{R}^3$ ,

$$\left\| \mathcal{M}^{-1} \begin{bmatrix} F \\ T \end{bmatrix} \right\| \leq 2(m^{-1}\|F\| + \|\mathcal{J}_0^{-1}\|\|T\|) \text{ for } m \geq \underline{m}, \text{ and } \lambda_i \geq \beta, i = 1, 2, 3, \quad (43)$$

2. some functions  $(v_i)_{i \in \{1, \dots, 6\}}$  in  $\widehat{\mathcal{V}}$  depending only on  $\mathcal{S}_0$ ,

such that there holds in  $L^2(0, T)$ :

$$\mathcal{M} \begin{bmatrix} \ell \\ r \end{bmatrix}' = (2\nu a(u, v_i) + b(u, u, v_i))_{i \in \{1, \dots, 6\}}. \quad (44)$$

*Proof.* The matrix  $\mathcal{M}$  is usually referred to as virtual inertia tensor, it incorporates the added mass of the solid  $\mathcal{M}_2$ , and is defined by

$$\mathcal{M}_1 := \begin{bmatrix} m \text{Id}_3 & 0 \\ 0 & \mathcal{J}_0 \end{bmatrix}, \quad \mathcal{M}_2 := \left[ \int_{\mathcal{F}_0} \nabla \Phi_i \cdot \nabla \Phi_j \, dx \right]_{i, j \in \{1, \dots, 6\}} \quad \text{and } \mathcal{M} := \mathcal{M}_1 + \mathcal{M}_2,$$

where the functions  $\Phi_i$ , usually referred to as the Kirchhoff potentials, as the solutions of the following problems:

$$\begin{aligned} -\Delta \Phi_i &= 0 \quad \text{for } x \in \mathcal{F}_0, \\ \Phi_i &\rightarrow 0 \quad \text{as } |x| \rightarrow \infty, \\ \frac{\partial \Phi_i}{\partial n} &= K_i \quad \text{for } x \in \partial \mathcal{S}_0, \end{aligned}$$

where

$$K_i := \begin{cases} n_i & \text{if } i = 1, 2, 3, \\ [x \wedge n]_{i-3} & \text{if } i = 4, 5, 6. \end{cases}$$

We observe that the matrix  $\mathcal{M}_2$  depends only on  $\mathcal{S}_0$  and is nonnegative symmetric so that  $\mathcal{M}$  depends only on  $\mathcal{S}_0$ ,  $m$  and  $\mathcal{J}_0$ , and is definite positive symmetric.

Now for any  $F$  and  $T$  in  $\mathbb{R}^3$ , let

$$\begin{bmatrix} x \\ y \end{bmatrix} := \mathcal{M}^{-1} \begin{bmatrix} F \\ T \end{bmatrix} = \begin{bmatrix} m^{-1} \text{Id}_3 & 0 \\ 0 & \mathcal{J}_0^{-1} \end{bmatrix} \left( \begin{bmatrix} F \\ T \end{bmatrix} - \mathcal{M}_2 \begin{bmatrix} x \\ y \end{bmatrix} \right).$$

Since  $\mathcal{M}_2$  depends only on  $\mathcal{S}_0$ , there exists  $C > 0$  depending only on  $\mathcal{S}_0$  such that  $\|\mathcal{M}_2 \begin{bmatrix} x \\ y \end{bmatrix}\| \leq C \|\begin{bmatrix} x \\ y \end{bmatrix}\|$ . Then, we can estimate

$$\left\| \begin{bmatrix} x \\ y \end{bmatrix} \right\| \leq m^{-1} \|F\| + \|\mathcal{J}_0^{-1}\| \|T\| + \max\{m^{-1}, \|\mathcal{J}_0^{-1}\|\} C \left\| \begin{bmatrix} x \\ y \end{bmatrix} \right\|.$$

It is therefore sufficient to take  $\underline{m} = \beta = 2C$  to obtain (43).

For  $i = 1, \dots, 6$ , we introduce the function  $v_i$  defined by

$$v_i := \nabla \Phi_i \text{ in } \mathcal{F}_0 \text{ and } v_i := \begin{cases} e_i & \text{if } i = 1, 2, 3, \\ e_{i-3} \wedge x & \text{if } i = 4, 5, 6, \end{cases} \text{ in } \mathcal{S}_0.$$

These functions only depend on  $\mathcal{S}_0$ . Moreover they are in  $\widehat{\mathcal{V}}$ . Observe in particular that  $\nabla v_i$  decays like  $1/|\cdot|^4$  at infinity so that  $\int_{\mathcal{F}_0} |\nabla v_i(y)|^2 (1 + |y|^2) dy < +\infty$ . We can therefore take them as test functions in (22). Indeed we apply (22) to  $v = v_i$  and we derive in time to obtain, for all  $t \in [0, T]$ ,

$$\partial_t (u, v_i)_{\mathcal{H}} = 2\nu a(u, v_i) + b(u, u, v_i). \quad (45)$$

Let us prove that

$$[(u, v_i)_{\mathcal{H}}]_{i,j \in \{1, \dots, 6\}} = \mathcal{M} \begin{bmatrix} \ell \\ r \end{bmatrix}. \quad (46)$$

To this end, we first use (21) to arrive at

$$[(u, v_i)_{\mathcal{H}}]_{i,j \in \{1, \dots, 6\}} = [\int_{\mathcal{F}_0} u \cdot \nabla \Phi_i]_{i,j \in \{1, \dots, 6\}} + \mathcal{M}_1 \begin{bmatrix} \ell \\ r \end{bmatrix}. \quad (47)$$

Then, using an integration by parts, we observe that

$$\int_{\mathcal{F}_0} u \cdot \nabla \Phi_i = \int_{\partial \mathcal{S}_0} (u \cdot n) \Phi_i = \int_{\partial \mathcal{S}_0} (u_{\mathcal{S}} \cdot n) \Phi_i,$$

so that, expanding  $u_{\mathcal{S}}$  and using another integration by parts, give us

$$[\int_{\mathcal{F}_0} u \cdot \nabla \Phi_i]_{i,j \in \{1, \dots, 6\}} = \mathcal{M}_2 \begin{bmatrix} \ell \\ r \end{bmatrix}. \quad (48)$$

Gathering (47) and (48) yields (46). Then combining (45) and (46) furnishes (44).

Therefore it only remains to prove that  $\ell$  and  $r$  are in  $H^1(0, T; \mathbb{R}^3)$ . Since the matrix  $\mathcal{M}$  is time-independent it is sufficient to prove that the right hand side of (44) is in  $L^2(0, T; \mathbb{R}^3)$ . Indeed this follows from (27), (42), from that  $(v_i)_{i \in \{1, \dots, 6\}}$  are in  $\widehat{\mathcal{V}}$  and that  $u$  is in  $C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \mathcal{Y})$ .  $\square$

Let us emphasize that this property seems to be a particularity of the case of the Navier conditions. In particular in the case of the no-slip conditions, the corresponding weak formulation involves test functions continuous across the body's boundary, a feature which is not satisfied by the functions  $v_i$ . To our knowledge the counterpart of Proposition 2 in the case of the no-slip conditions is not known.

The estimate (43) will be useful for the next section. It is also interesting for the sequel to observe that

$$(b(u, u, v_i))_{i \in \{1, \dots, 6\}} = \begin{bmatrix} m r \wedge \ell \\ (\mathcal{J}_0 r) \wedge r \end{bmatrix} + \left( \int_{\mathcal{F}_0} \left( [(u - u_{\mathcal{S}}) \cdot \nabla] \nabla \Phi_i \right) \cdot u - \det(r_u, u, \nabla \Phi_i) \right)_{i \in \{1, \dots, 6\}}. \quad (49)$$

### 3.5 The infinite inertia limit

Let us also mention that Theorem 1 extends to the case of a moving body some earlier results, in particular see [7, 27], about the existence of Leray solutions in the case where Navier conditions are considered but on a fixed boundary. In this case, the system reads

$$\frac{\partial u}{\partial t} + u \cdot \nabla u + \nabla p = \nu \Delta u \quad \text{for } x \in \mathcal{F}_0, \quad (50)$$

$$\operatorname{div} u = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (51)$$

$$u \cdot n = 0 \quad \text{for } x \in \partial \mathcal{S}_0, \quad (52)$$

$$(D(u)n) \wedge n = -\alpha u \wedge n \quad \text{for } x \in \partial \mathcal{S}_0, \quad (53)$$

$$u|_{t=0} = u_0, \quad (54)$$

and a weak Leray solution of (50)-(54) is by definition a function

$$u \in C_w([0, T]; L^2_\sigma(\mathcal{F}_0)) \cap L^2(0, T; H^1(\mathcal{F}_0)),$$

such that

1. for all  $v \in H^1(0, T; L^2_\sigma(\mathcal{F}_0)) \cap L^4(0, T; H^1(\mathcal{F}_0))$ , and for all  $t \in [0, T]$ ,

$$\int_{\mathcal{F}_0} u(t, \cdot) \cdot v(t, \cdot) dx - \int_{\mathcal{F}_0} u_0 \cdot v|_{t=0} dx = \int_0^t \left[ \int_{\mathcal{F}_0} u \cdot \partial_t v dx + 2\nu a^*(u, v) + b^*(u, u, v) \right], \quad (55)$$

where

$$a^*(u, v) := -\alpha \int_{\partial \mathcal{S}_0} u \cdot v - \int_{\mathcal{F}_0} D(u) : D(v), \quad \text{and} \quad b^*(u, v, w) := \int_{\mathcal{F}_0} [u \cdot \nabla w] \cdot v,$$

2. for any  $t \in [0, T]$ ,

$$\frac{1}{2} \|u(t, \cdot)\|_{L^2(\mathcal{F}_0)}^2 + 2\nu \int_{(0,t) \times \mathcal{F}_0} |D(u)|^2 + 2\alpha\nu \int_0^t \int_{\partial \mathcal{S}_0} |u|^2 \leq \frac{1}{2} \|u_0\|_{L^2(\mathcal{F}_0)}^2. \quad (56)$$

Here,  $L^2_\sigma(\mathcal{F}_0)$  denotes the space of the divergence free vector fields in  $L^2(\mathcal{F}_0)$  which are tangent to the solid's boundary  $\partial \mathcal{S}_0$ .

The following result shows that the case with the body fixed can be thought as *the limit of infinite inertia*, that is, when  $m$  and the eigenvalues  $(\lambda_i)_{i=1,2,3}$  of  $\mathcal{J}_0$  converge to  $+\infty$  with  $\lambda_i = O(\lambda_j)$  for any  $i, j$ . This last condition is quite natural if one thinks that the solid density  $\rho_{\mathcal{S}_0}$  is multiplied by a factor converging to  $+\infty$  in (1) and (3). This condition can alternatively be written as  $\|\mathcal{J}_0\| = O(\|\mathcal{J}_0^{-1}\|^{-1})$  (using the spectral norms introduced in Section 3.4).

Let us point out that  $\|\mathcal{M}^{-1}\|_{\mathbb{R}^6 \times 6} \rightarrow 0$  as  $m$  and  $(\lambda_i)_{i=1,2,3}$ , converge to  $+\infty$ , as a consequence of the estimate (43), and therefore in particular  $\|\mathcal{M}^{-1}\|_{\mathbb{R}^6 \times 6} \rightarrow 0$  in the infinite inertia limit. Another observation that will be useful is that there holds for any  $r \in \mathbb{R}^3$ ,

$$\|(\mathcal{J}_0 r) \wedge r\| \leq C(\mathcal{J}_0 r) \cdot r, \quad (57)$$

for a constant  $C > 0$ , uniform in the infinite inertia limit.

Indeed, introducing some normalized eigenvectors  $(r_i)_{i=1,2,3}$ , associated to  $(\lambda_i)_{i=1,2,3}$ , respectively, we can write for some real coefficients  $(\alpha_i)_{i=1,2,3}$ , that  $r = \sum_{i=1}^3 \alpha_i r_i$  and therefore  $(\mathcal{J}_0 r) \wedge r = \sum_{i,j} \alpha_i \alpha_j \lambda_i (r_i \wedge r_j)$ . So that, for some constants uniform in the infinite inertia limit, one has:

$$\|(\mathcal{J}_0 r) \wedge r\| \leq C \sum_{i,j} |\alpha_i| |\alpha_j| \lambda_i \leq C' \sum_{i,j} |\alpha_i| |\alpha_j| \sqrt{\lambda_i} \sqrt{\lambda_j} \leq C'' \left( \sum_i |\alpha_i| \sqrt{\lambda_i} \right)^2 \leq C''' \sum_i \alpha_i^2 \lambda_i = C'''' (\mathcal{J}_0 r) \cdot r.$$

**Theorem 2.** *Let be given  $u_0 \in \mathcal{H}$  with  $\ell_0 = r_0 = 0$  and  $T > 0$ . For any  $m$  and  $\mathcal{J}_0$  we consider a weak solution  $u$  of (12)-(19) in  $C_w([0, T]; \mathcal{H}) \cap L^2(0, T; \mathcal{Y})$  given by Theorem 1. Then in the infinite inertia limit,  $u|_{\mathcal{F}_0}$  converges, up to a subsequence, in  $L^2(0, T; L^2_{loc}(\mathcal{F}_0))$  to a weak solution of (50)-(54) and  $\ell$  and  $r$  converge to 0 in  $H^1(0, T; \mathbb{R}^3)$ .*

*Proof.* We infer from (28) that  $u$  is bounded in  $L^\infty(0, T; \mathcal{H}) \cap L^2(0, T; \mathcal{Y})$  uniformly with respect to the inertia. Not only that but we also obtain that  $\ell$  and  $r$  converge to 0 in  $L^\infty(0, T; \mathbb{R}^3)$  in the infinite inertia limit, because  $(\mathcal{J}_0 r) \cdot r \geq \min(\lambda_i) \|r\|^2$ .

The following lemma is quite simple to establish but will be useful in the sequel.

**Lemma 2.** *Let  $u$  be as in Theorem 2. Then for any  $v \in H^1(0, T; L^2_\sigma(\mathcal{F}_0)) \cap L^4(0, T; \tilde{\mathcal{V}})$ , for any  $t \in [0, T]$ ,*

$$\int_{\mathcal{F}_0} u(t, \cdot) \cdot v(t, \cdot) dx - \int_{\mathcal{F}_0} u_0 \cdot v|_{t=0} dx = \int_0^t \left[ \int_{\mathcal{F}_0} u \cdot \partial_t v dx + 2\nu a^*(u, v) + b^*(u, u, v) + F(u, v) \right], \quad (58)$$

where

$$F(u, v) := 2\alpha\nu \int_{\partial\mathcal{S}_0} u_S \cdot v - \int_{\mathcal{F}_0} \left( [u_S \cdot \nabla v] \cdot u - \det(r_u, u, v) \right).$$

Above  $\tilde{\mathcal{V}}$  denotes the space

$$\tilde{\mathcal{V}} := \left\{ \phi \in L^2_\sigma(\mathcal{F}_0) / \int_{\mathcal{F}_0} |\nabla \phi(y)|^2 (1 + |y|^2) dy < +\infty \right\},$$

endowed with the norm

$$\|\phi\|_{\tilde{\mathcal{V}}} := \|\phi\|_{L^2(\mathcal{F}_0)} + \|\nabla \phi\|_{L^2(\mathcal{F}_0, (1+|y|^2)^{\frac{1}{2}} dy)}.$$

*Proof of Lemma 2.* It is sufficient to extend  $v$  by 0 in  $\mathcal{S}_0$  to obtain a function in  $H^1(0, T; \mathcal{H}) \cap L^4(0, T; \mathcal{V})$  which is used as a test function in (22). This provides (58).  $\square$

Then, proceeding as in Section 3.3, we obtain a bound of  $\partial_t u|_{\mathcal{F}_0}$  in  $L^{\frac{4}{3}}(0, T; \tilde{\mathcal{V}}')$  which is uniform in the infinite inertia limit. We therefore deduce that the sequence of weak solutions  $u$  is relatively compact in  $L^2(0, T; L^2_{loc}(\mathcal{F}_0))$ . Thus the restrictions of  $u$  to  $\mathcal{F}_0$  converge, up to a subsequence, to a limit  $u^*$  weakly-\* in  $L^\infty(0, T; L^2(\mathcal{F}_0))$ , weakly in  $L^2(0, T; H^1(\mathcal{F}_0))$  and strongly in  $L^2(0, T; L^2_{loc}(\mathcal{F}_0))$ .

Let us now prove that  $u^*$  is a weak solution of (50)-(54). We deduce from the above convergence that  $F(u, v)$  converges to 0 in  $L^1(0, T)$ , and passing to limit in the other terms of (58) we can conclude that  $u^*$  satisfies (55) for any  $v \in H^1(0, T; L^2_\sigma(\mathcal{F}_0)) \cap L^4(0, T; H^1(\mathcal{F}_0))$  such that  $\int_{\mathcal{F}_0} |\nabla v(y)|^2 (1 + |y|^2) dy < +\infty$ . Then one easily remove this last condition by using Lebesgue's dominated convergence theorem. Thus  $u^*$  is a weak solution of (50)-(54).

In order to finish the proof of Theorem (2) it only remains to prove that  $\ell'$  and  $r'$  converge to 0 in  $L^2(0, T; \mathbb{R}^3)$ . This relies on the regularity property established in the previous section. Indeed we define, for  $i \in \{1, \dots, 6\}$ ,

$$\mathcal{T}_{1,i} := \int_{\mathcal{F}_0} \left( [(u - u_S) \cdot \nabla] \nabla \Phi_i \cdot u - \det(r_u, u, \nabla \Phi_i) \right),$$

and  $\mathcal{T}_2 := \begin{bmatrix} m r \wedge \ell \\ (\mathcal{J}_0 r) \wedge r \end{bmatrix}$ , so that from (44) and (49) we infer that

$$\begin{bmatrix} \ell \\ r \end{bmatrix}' = 2\nu \mathcal{M}^{-1} (a(u, v_i))_{i \in \{1, \dots, 6\}} + \mathcal{M}^{-1} (\mathcal{T}_{1,i})_{i \in \{1, \dots, 6\}} + \mathcal{M}^{-1} \mathcal{T}_2. \quad (59)$$

Since  $u$  is bounded in  $L^\infty(0, T; \mathcal{H}) \cap L^2(0, T; \mathcal{Y})$ , the functions  $(v_i)_{i \in \{1, \dots, 6\}}$  are in  $\tilde{\mathcal{V}}$  and depend only on  $\mathcal{S}_0$ , and  $\|\mathcal{M}^{-1}\|_{\mathbb{R}^{6 \times 6}} \rightarrow 0$  in the infinite inertia limit, we infer easily from (27) that the first term of the right hand side of (59) vanishes in  $L^2(0, T; \mathbb{R}^6)$  in the infinite inertia limit.

On the other hand we can bound the second term as follows: for any  $i \in \{1, \dots, 6\}$ , for any  $t$ ,  $\|\mathcal{T}_{1,i}\| \leq C(\|u\|_{L^2(\mathcal{F}_0)}^2 + \|\ell\|^2 + \|r\|^2)$ . Hence, thanks to the energy bound, we get that  $\mathcal{T}_{1,i}$  is bounded in the infinite inertia limit. Therefore the second term of the right hand side of (59) also vanishes in  $L^2(0, T; \mathbb{R}^6)$  in the infinite inertia limit.

Finally, in order to deal with the last term, we use the estimate (43) to bound, for any  $t$ ,

$$\begin{aligned}\|\mathcal{M}^{-1}\mathcal{T}_2\| &\leq 2\left(\|r \wedge \ell\| + (\min(\lambda_i))^{-1}\|(\mathcal{J}_0 r) \wedge r\|\right) \\ &\leq C\left(\|\ell\|^2 + \|r\|^2 + (\min(\lambda_i))^{-1}(\mathcal{J}_0 r) \cdot r\right),\end{aligned}$$

thanks to (57). We thus deduce from the energy bound that the last term of the right hand side of (59) also vanishes in  $L^2(0, T; \mathbb{R}^6)$  in the infinite inertia limit.

The proof of Theorem 2 is then complete.  $\square$

## 4 Smooth local-in-time solutions of the inviscid system

In this section we consider the system “inviscid incompressible fluid + rigid body”.

### 4.1 The system “inviscid incompressible fluid + rigid body”

When the viscosity coefficient  $\nu$  is set equal to 0, formally, the system (4)-(11) degenerates into the following equations:

$$\frac{\partial U^E}{\partial t} + (U^E \cdot \nabla)U^E + \nabla P^E = 0 \quad \text{for } x \in \mathcal{F}^E(t) = \mathbb{R}^3 \setminus \mathcal{S}^E(t), \quad (60)$$

$$\operatorname{div} U^E = 0 \quad \text{for } x \in \mathcal{F}^E(t), \quad (61)$$

$$U^E \cdot n = U_S^E \cdot n \quad \text{for } x \in \partial\mathcal{S}^E(t), \quad (62)$$

$$m(h^E)'' = \int_{\partial\mathcal{S}^E(t)} P^E n \, ds, \quad (63)$$

$$(\mathcal{J}^E R^E)' = \int_{\partial\mathcal{S}^E(t)} P^E (x - h^E(t)) \wedge n \, ds, \quad (64)$$

$$U^E|_{t=0} = U_0^E, \quad (65)$$

$$h^E(0) = 0, \quad (h^E)'(0) = \ell_0^E, \quad R^E(0) = r_0^E, \quad (66)$$

where the solid velocity is given by

$$U_S^E(t, x) := (h^E)'(t) + R^E(t) \wedge (x - h^E(t)),$$

and

$$\mathcal{S}^E(t) := \eta^E(t, \cdot)(\mathcal{S}_0), \quad \text{with } \eta^E(t, x) := h^E(t) + Q^E(t)x,$$

where the matrix  $Q^E$  solves the differential equation

$$(Q^E)'x = R^E \wedge (Q^E x) \quad \text{with } Q^E(0)x = x, \quad \text{for any } x \in \mathbb{R}^3.$$

Finally  $\mathcal{J}^E$  is given by

$$\mathcal{J}^E = Q^E \mathcal{J}_0 (Q^E)^T.$$

Observe that we prescribe  $h^E(0) = 0$  so that the initial position  $\mathcal{S}^E(0)$  occupied by the solid also starts from  $\mathcal{S}_0$  at  $t = 0$ . The mass  $m$  and the initial inertial matrix  $\mathcal{J}_0$  are also the same than in the previous case of the Navier-Stokes equations.

Let us emphasize that in the boundary condition (62) there is only an impermeability condition, the slip-with-friction condition is no more prescribed. This loss of boundary condition generates a boundary layer which makes difficult the issue of the inviscid limit of the system since the fluid flow is drastically modified in a neighborhood of the body’s boundary of thickness proportional to  $\sqrt{\nu}$ . The main goal of the paper is precisely to show that despite these layers the solution of (4)-(11) converges in a rather good manner to the solution of (60)-(66) as  $\nu \rightarrow 0$ . This will be achieved in the next section. Here we will first gather a few results about the inviscid system (60)-(66).

## 4.2 A change of variables

To write the system in a fixed domain, we perform the following change of coordinates:

$$\begin{aligned} \ell^E(t) &:= Q^E(t)^T (h^E)'(t), \quad R^E(t) := Q^E(t)r^E(t), \\ u^E(t, x) &:= Q^E(t)^T U^E(t, Q^E(t)x + h^E(t)) \quad \text{and} \quad p^E(t, x) := P^E(t, Q^E(t)x + h^E(t)), \end{aligned}$$

where  $Q^E(t)$  is the rotation matrix associated to the motion of  $\mathcal{S}^E(t)$  defined in the previous section.

Observe that this change of variable is analogous to the one that we have used for the Navier-Stokes equations in Section 3.1.

The system (60)-(66) now reads

$$\frac{\partial u^E}{\partial t} + (u^E - u_S^E) \cdot \nabla u^E + r^E \wedge u^E + \nabla p^E = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (67)$$

$$\operatorname{div} u^E = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (68)$$

$$u^E \cdot n = u_S^E \cdot n \quad \text{for } x \in \partial\mathcal{S}_0, \quad (69)$$

$$m(\ell^E)' = \int_{\partial\mathcal{S}_0} p^E n \, ds + (m\ell^E) \wedge r^E, \quad (70)$$

$$\mathcal{J}_0(r^E)' = \int_{\partial\mathcal{S}_0} p^E x \wedge n \, ds + (\mathcal{J}_0 r^E) \wedge r^E, \quad (71)$$

$$u^E|_{t=0} = u_0^E, \quad (72)$$

$$h^E(0) = 0, \quad (h^E)'(0) = \ell_0^E, \quad r^E(0) = r_0^E, \quad (73)$$

with

$$u_S^E(t, x) := \ell^E(t) + r^E(t) \wedge x. \quad (74)$$

## 4.3 Smooth local-in-time solutions

Let us recall the following result from [38] about the existence and uniqueness of classical solutions to the equations (67)-(73), where, as previously, we extend the initial data  $u_0^E$  by setting  $u_0^E := \ell_0^E + r_0^E \wedge x$  for  $x \in \mathcal{S}_0$ .

**Theorem 3.** *Let be given  $\lambda \in (0, 1)$  and  $u_0^E \in \mathcal{H}$  such that  $u_0^E|_{\mathcal{F}_0} \in H^1 \cap C^{1,\lambda}$  and  $\operatorname{curl} u_0^E|_{\mathcal{F}_0}$  is compactly supported. Then there exist  $T > 0$  and a unique solution  $u^E$  of (67)-(73) in  $C^1([0, T]; \mathcal{H})$  such that  $(\nabla u^E)|_{[0, T] \times \mathcal{F}_0} \in C([0, T]; L^2(\mathcal{F}_0, (1 + |x|^2)^{\frac{1}{2}} dx)) \cap C_{w*}([0, T]; C^{0,\lambda}(\mathcal{F}_0))$ . Moreover for any  $t \in [0, T]$ ,*

$$\|u^E(t, \cdot)\|_{\mathcal{H}}^2 = \|u_0^E\|_{\mathcal{H}}^2. \quad (75)$$

Here,  $C^{k,\lambda}(\mathcal{F}_0)$ ,  $k \in \mathbb{N}$ ,  $\lambda \in (0, 1)$ , denotes the usual Hölder space.

A few comments are in order.

It is worth to point out here that the solution  $u^E$  given by Theorem 3 satisfies the following property: for any  $t \in [0, T]$ , for any  $v \in \underline{\mathcal{V}}$ , there holds

$$(\partial_t u^E, v)_{\mathcal{H}} = -b(u^E, v, u^E). \quad (76)$$

To see that, multiply (67) by  $v$  and integrate by parts in space using (68)-(69).

It is useful for the sequel to recall that the proof given in [38] of Theorem 3 relies on the following vorticity

reformulation of (67)-(73):

$$\partial_t \omega^E + (u^E - u_S^E) \cdot \nabla \omega^E = (\omega^E \cdot \nabla)(u^E - u_S^E) \quad \text{in } [0, T] \times \mathcal{F}_0, \quad (77)$$

$$\begin{cases} \operatorname{curl} u^E = \omega^E & \text{in } [0, T] \times \mathcal{F}_0, \\ \operatorname{div} u^E = 0 & \text{in } [0, T] \times \mathcal{F}_0, \\ u^E \cdot n = u_S^E \cdot n & \text{on } [0, T] \times \partial \mathcal{S}_0, \\ u^E \rightarrow 0 & \text{for } |x| \rightarrow \infty, \end{cases} \quad (78)$$

$$u_S^E(t, x) := \ell^E(t) + r^E(t) \wedge x \quad \text{in } [0, T] \times \mathbb{R}^3, \quad (79)$$

$$\mathcal{M} \begin{bmatrix} \ell^E \\ r^E \end{bmatrix}' = (b(u^E, u^E, v_i))_{i \in \{1, \dots, 6\}}, \quad (80)$$

where  $\mathcal{M}$  and  $v_i$  were introduced in Section 3.4.

The vorticity equation (77) can easily be inferred from (67), (68) and (74) whereas (80) is obtained from (26), (76) and some integration by parts. Observe that (80) can be seen as the inviscid counterpart of (44), and recall that the  $b(u^E, u^E, v_i)$  can be computed thanks to the formula (49).

#### 4.4 The infinite inertia limit

The following result is the counterpart of Theorem 2 for the inviscid system (67)-(73). It shows that in the limit of infinite inertia, that is, when  $m$  and the eigenvalues  $(\lambda_i)_{i=1,2,3}$  of  $\mathcal{J}_0$  converge to  $+\infty$  with  $\lambda_i = O(\lambda_j)$  for any  $i, j$ , the system (67)-(73) degenerates into the following classical Euler equations in  $\mathcal{F}_0$ :

$$\frac{\partial u^E}{\partial t} + u^E \cdot \nabla u^E + \nabla p^E = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (81)$$

$$\operatorname{div} u^E = 0 \quad \text{for } x \in \mathcal{F}_0, \quad (82)$$

$$u^E \cdot n = 0 \quad \text{for } x \in \partial \mathcal{S}_0, \quad (83)$$

$$u^E|_{t=0} = u_0^E. \quad (84)$$

**Theorem 4.** *Let be given  $\lambda \in (0, 1)$  and  $u_0^E \in \mathcal{H}$  such that  $\ell_0^E = r_0^E = 0$ ,  $u_0^E|_{\mathcal{F}_0} \in H^1 \cap C^{1,\lambda}$  and  $\operatorname{curl} u_0^E|_{\mathcal{F}_0}$  is compactly supported. Let be given  $\underline{m} > 0$  and  $\beta > 0$ .*

*Then there exists  $T > 0$  such that for any  $m \geq \underline{m}$  and for any symmetric positive  $3 \times 3$  matrix  $\mathcal{J}_0$  with eigenvalues  $(\lambda_i)_{i=1,2,3}$  satisfying  $\lambda_i \geq \beta$ , the corresponding solution  $u^E$  of (67)-(73) given by Theorem 3 is defined up to the time  $T$ .*

*Moreover in the infinite inertia limit,  $u^E|_{\mathcal{F}_0}$  converges in  $L^\infty(0, T; C^{1,\tilde{\lambda}}(\mathcal{F}_0))$ , for any  $\tilde{\lambda} \in (0, \lambda)$ , to the unique smooth solution of (81)-(84) and  $\ell^E$  and  $r^E$  converge to 0 in  $C^1(0, T; \mathbb{R}^3)$ .*

*Proof.* The key issue here is to obtain some estimates uniform in the infinite inertia limit. Let us stress in particular that, a priori, Theorem 3 only provides, for some inertia  $m$  and  $\mathcal{J}_0$ , the existence of a smooth solution on a time interval  $[0, T_{m, \mathcal{J}_0}]$  which may shrink when  $m$  and the eigenvalues  $(\lambda_i)_{i=1,2,3}$  of  $\mathcal{J}_0$  go to infinity. However we are going to see below that this is not the case. Actually revisiting the proof of Theorem 3 given in [38] we will provide a time  $T$  common to any large enough inertia.

The first basic observation in this direction is that according to the energy identity (75), and because of the choice of the initial data (which are somehow “well-prepared”) the energy  $\|u^E(t, \cdot)\|_{\mathcal{H}}^2$  does not depend on time nor on the inertia:

$$\int_{\mathcal{F}_0} |u^E(t, \cdot)|^2 dx + m \ell^E(t) \cdot \ell^E(t) + \mathcal{J}_0 r^E(t) \cdot r^E(t) = \int_{\mathcal{F}_0} |u_0^E|^2 dx. \quad (85)$$

Let us now show how to obtain a uniform estimate of the velocity in  $L^\infty(0, T; C^{1,\lambda}(\mathcal{F}_0))$  for some  $T > 0$ , thanks to the vorticity formulation (77)-(80).

By standard transport estimates (cf. [20], Corollary 2.4) one infers from (77) the estimate

$$\begin{aligned} \|\omega^E(t)\|_{C^{0,\lambda}(\mathcal{F}_0)} &\leq \|\omega_0^E\|_{C^{0,\lambda}(\mathcal{F}_0)} \exp\left(C \int_0^t (\|u^E\|_{C^{1,\lambda}(\mathcal{F}_0)}(s) + \|r^E\|(s)) ds\right) \\ &\leq \|u_0^E\|_{C^{1,\lambda}(\mathcal{F}_0)} \exp(C \|r^E\|_{L^\infty(0,T)} t) \exp\left(C \int_0^t \|u^E\|_{C^{1,\lambda}(\mathcal{F}_0)}(s) ds\right), \end{aligned} \quad (86)$$

where  $C$  does not depend on the inertia.

On the other hand by classical elliptic theory, one infers from (78) the following estimate, where time is omitted,

$$\|u^E\|_{C^{1,\lambda}(\mathcal{F}_0)} \leq C(\|\omega^E\|_{C^{0,\lambda}(\mathcal{F}_0)} + \|\ell^E\| + \|r^E\|) \leq C(\|\omega^E\|_{C^{0,\lambda}(\mathcal{F}_0)} + \|u_0^E\|_{L^2(\mathcal{F}_0)}), \quad (87)$$

with  $C > 0$  depending on  $\underline{m} > 0$  and  $\beta > 0$ .

Plugging (87) in (86) yields,

$$\|\omega^E(t)\|_{C^{0,\lambda}(\mathcal{F}_0)} \leq \|u_0^E\|_{C^{1,\lambda}(\mathcal{F}_0)} \exp(C\|u_0^E\|_{L^2(\mathcal{F}_0)}t) \exp\left(C \int_0^t \|\omega^E\|_{C^{0,\lambda}(\mathcal{F}_0)}(s)ds\right),$$

with  $C > 0$  depending on  $\underline{m} > 0$  and  $\beta > 0$ , from which one deduces the existence of a small time  $T > 0$  and an estimate of velocity in  $L^\infty(0, T; C^{1,\lambda}(\mathcal{F}_0))$  both uniformly for any  $m \geq \underline{m}$  and for any symmetric positive  $3 \times 3$  matrix  $\mathcal{J}_0$  with eigenvalues  $(\lambda_i)_{i=1,2,3}$  satisfying  $\lambda_i \geq \beta$ .

Let us now prove the second part of Theorem 4 about convergence of the fluid and solid velocities. First (85) yields that  $\ell^E$  and  $r^E$  converge to 0 in  $L^\infty(0, T; \mathbb{R}^3)$  in the infinite inertia limit. Then, similarly as we proceed in the proof of Theorem 2, by using (80) and (49) we write

$$\begin{bmatrix} \ell^E \\ r^E \end{bmatrix}' = \mathcal{M}^{-1}(\mathcal{T}_{1,i}^E)_{i \in \{1, \dots, 6\}} + \mathcal{M}^{-1}\mathcal{T}_2^E.$$

where,

$$\mathcal{T}_{1,i}^E := \int_{\mathcal{F}_0} \left( [(u^E - u_S^E) \cdot \nabla] \nabla \Phi_i \cdot u^E - \det(r_u^E, u^E, \nabla \Phi_i) \right), \text{ and } \mathcal{T}_2^E := \begin{bmatrix} m r^E \wedge \ell^E \\ (\mathcal{J}_0 r^E) \wedge r^E \end{bmatrix}.$$

Thus, by using again the energy bound (85), we deduce that  $\ell^E$  and  $r^E$  converge to 0 in  $C^1(0, T; \mathbb{R}^3)$ .

Finally it remains to prove that  $u^E|_{\mathcal{F}_0}$  converges, up to a subsequence, in  $L^\infty(0, T; C^{1,\tilde{\lambda}}(\mathcal{F}_0))$ , for any  $\tilde{\lambda} \in (0, \lambda)$ . Since we have some uniform estimates of  $u^E|_{\mathcal{F}_0}$  in the space  $L^\infty(0, T; C^{1,\lambda}(\mathcal{F}_0))$ , it is sufficient to obtain a temporal estimate uniform in infinite inertia limit and to use the Aubin-Lions lemma to conclude that a subsequence is converging in  $L^\infty(0, T; C^{1,\tilde{\lambda}}(\mathcal{F}_0))$ , for any  $\tilde{\lambda} \in (0, \lambda)$ . This can be easily achieved by using (76) with some test functions  $v$  compactly supported in  $\mathcal{F}_0$ .

These convergences are sufficient to yield that the limit is a smooth solution of (81)-(84) on  $[0, T]$ .

Since classical solutions of the Euler equations are unique we finally deduce that the whole sequence is converging.  $\square$

## 5 Inviscid limit

Let us now state the main result of this paper.

**Theorem 5.** *The following holds true.*

1. *With the notations of Theorem 1 and Theorem 3, and assuming that  $u_0$  converges to  $u_0^E$  in  $\mathcal{H}$  when  $\nu$  tends to 0 and that  $\alpha := \alpha^\nu$  satisfies  $\alpha\nu$  converges to 0 when  $\nu$  tends to 0, then  $u$  converges to  $u^E$  in  $L^\infty(0, T; \mathcal{H})$ ,  $\sqrt{\nu}\|u|_{\mathcal{F}_0}\|_{L^2(0,T;H^1(\mathcal{F}_0))}$  and  $\sqrt{\alpha\nu}\|u - u_S\|_{L^2((0,T)\times\partial S_0)}$  converge to 0, where  $T > 0$  is the lifetime of the smooth solution  $u^E$  of the inviscid system*
2. *Moreover  $(\ell, r)$  converges to  $(\ell^E, r^E)$  in  $H^1(0, T; \mathbb{R}^6)$ .*
3. *Assuming that  $u_0 = u_0^E$  and that  $\alpha > 0$  does not depend on  $\nu$ , then there exists  $C > 0$  (depending on  $T$ ) such that*

$$\|u - u^E\|_{L^\infty(0,T;\mathcal{H})} + \sqrt{\nu}\|u - u^E\|_{L^2(0,T;H^1(\mathcal{F}_0))} \leq C(1 + \alpha)\nu^{3/4}. \quad (88)$$

A few remarks are in order.

Regarding the first part of Theorem 5, let us first mention again the references [10, 30, 1] for the relevance of considering a friction coefficient depending on the viscosity, as a limit of accommodation boundary condition for the Boltzmann equation. The first part of Theorem 5 extends earlier results where a fixed boundary was considered,

see [26, 34, 1, 41]. Let us point out in particular that it could be possible to extend the first part of Theorem 5 to a weaker setting, following the analysis of [1]. This will require to extend P.-L. Lions' definition of dissipative solutions of the Euler incompressible equations to the system (67)-(73), and to modify the proof of the first part of Theorem 5 below following a by now classical method, so-called the relative entropy method or the modulated energy method depending on the context and on the authors. We choose here to consider smooth solutions of the system (67)-(73) in order to keep the unity of the theorem, since the other parts fail in a weaker context.

The second part of Theorem 5 is perhaps the most surprising. It shows that the convergence of the body's dynamics is better than the one implied by the convergence of  $u$  to  $u^E$  in the energy space  $L^\infty(0, T; \mathcal{H})$  stated in the first part. Indeed the latter provides a convergence  $(\ell, r)$  to  $(\ell^E, r^E)$  in  $L^\infty(0, T; \mathbb{R}^6)$ . This last result can be seen a new avatar of a well-known phenomenon in the theory of the systems involving an incompressible flow and a structure, namely the added mass phenomenon, cf. for instance [6, 17].

If we focus on the dependence on the viscosity the estimate (88) says that  $u$  converges strongly to  $u^E$  in  $L^\infty(0, T; L^2(\mathcal{F}_0))$  with a rate of  $O(\nu^{3/4})$  and in  $L^2(0, T; H^1(\mathcal{F}_0))$  with a rate of  $O(\nu^{1/4})$ . We therefore recover the optimal rate of convergence, with respect to  $\nu$ , found in [27] in the case where the Navier conditions are prescribed on a fixed boundary.

Theorem 5 may be useful for controllability issues, in particular for the global controllability of the system. In the case of a fixed boundary a strategy initiated by Coron in [11] proved the global approximate controllability for the 2-D incompressible Navier-Stokes equations with Navier slip boundary conditions. His proof relies on another of his earlier results about the global controllability of the incompressible Euler equations, see [12]. This strategy was used later on by Chapouly in [5] to extend Coron's result into a global null controllability result.

It is therefore possible that a similar strategy could be fruitful in the case of a moving rigid body. Note however that in such a case little is known so far about the controllability of the inviscid system. Let us mention in that direction the results by Chambrion *et al.* [4] in the irrotational case.

## 6 Proof of Theorem 5

### 6.1 Two basic observations

Let us observe first that when  $u$  converges to  $u^E$  in  $L^\infty(0, T; \mathcal{H})$  then it follows straightforwardly from (28), (75) and Korn inequality that  $\sqrt{\nu}\|u|_{\mathcal{F}_0}\|_{L^2(0, T; H^1(\mathcal{F}_0))}$  and  $\sqrt{\alpha\nu}\|u - u_S\|_{L^2((0, T) \times \partial S_0)}$  converge to 0.

Moreover the second part of Theorem 5 is quite easy to obtain once the first part has been proved. Indeed, using that  $u$  converges to  $u^E$  in  $L^\infty(0, T; \mathcal{H})$ , and that  $\sqrt{\nu}\|u|_{\mathcal{F}_0}\|_{L^2(0, T; H^1(\mathcal{F}_0))}$  and  $\sqrt{\alpha\nu}\|u - u_S\|_{L^2((0, T) \times \partial S_0)}$  converge to 0 as  $\nu$  tends to 0, (44), (80) and (49), we obtain that  $\mathcal{M} \begin{bmatrix} \ell \\ r \end{bmatrix}'$  converges to  $\mathcal{M} \begin{bmatrix} \ell^E \\ r^E \end{bmatrix}'$  in  $L^2(0, T)$ . We then infer easily the second part.

### 6.2 Proof of the first part

Let us now turn to the proof of the first part. In the following,  $C$  will denote a constant independent of  $\nu$  and  $\alpha$  that may change from one relation to another.

Let us also introduce the difference

$$w := u - u^E \text{ and similarly for the initial condition } w_0 := u_0 - u_0^E.$$

In the solid we will use the notation

$$w_S := u_S - u_S^E.$$

For any  $t \in [0, T]$ , we have, thanks to (28) and (75),

$$\|w(t, \cdot)\|_{\mathcal{H}}^2 \leq \|u_0\|_{\mathcal{H}}^2 + \|u_0^E\|_{\mathcal{H}}^2 - 2(u, u^E)_{\mathcal{H}}(t) + 4\nu \int_0^t a(u, u).$$

We now apply (22) to  $v = u^E$  to get

$$\begin{aligned} (u, u^E)_{\mathcal{H}}(t) - (u_0, u_0^E)_{\mathcal{H}} &= \int_0^t \left[ (u, \partial_t u^E)_{\mathcal{H}} + 2\nu a(u, u^E) + b(u, u, u^E) \right] ds \\ &= \int_0^t \left[ 2\nu a(u, u^E) + b(u, u, u^E) - b(u^E, u, u^E) \right] ds, \end{aligned}$$

using (76) with  $v = u$ .

Therefore,

$$\begin{aligned} \|w(t, \cdot)\|_{\mathcal{H}}^2 &\leq \|w_0\|_{\mathcal{H}}^2 - 2 \int_0^t \left[ 2\nu a(u, u^E) - 2\nu a(u, u) + b(u, u, u^E) - b(u^E, u, u^E) \right] ds \\ &= \|w_0\|_{\mathcal{H}}^2 - 2 \int_0^t \left[ -2\nu a(u, w) + b(w, w, u^E) \right] ds. \end{aligned}$$

This can be recast as follows:

$$\|w(t, \cdot)\|_{\mathcal{H}}^2 + 4\alpha\nu \int_0^t \int_{\partial\mathcal{S}_0} |w - w_S|^2 + 4\nu \int_0^t \int_{\mathcal{F}_0} |D(w)|^2 \leq \|w_0\|_{\mathcal{H}}^2 - 2 \int_0^t \left[ -2\nu a(u^E, w) + b(w, w, u^E) \right] ds. \quad (89)$$

Therefore it only remains to use the Cauchy-Schwarz and Young inequalities, (42) and finally the Gronwall Lemma to achieve the first part of the theorem.

### 6.3 Proof of the last part

If one is interested in getting a better rate of convergence (for fixed  $\alpha$ ) a further treatment of the viscous part of the right hand side of (89) is needed. The underlying idea is somehow to put more derivatives on the inviscid solution  $u^E$ .

We use Lemma 1 to obtain

$$\begin{aligned} a(u^E, w) &= -\alpha \int_{\partial\mathcal{S}_0} (u^E - u_S^E) \cdot (w - w_S) - \int_{\mathcal{F}_0} D(u^E) \cdot D(w) \\ &= -\alpha \int_{\partial\mathcal{S}_0} (u^E - u_S^E) \cdot (w - w_S) + \frac{1}{2} \int_{\mathcal{F}_0} \Delta u^E \cdot w - \int_{\partial\mathcal{S}_0} \left( (D(u^E)n) \wedge n \right) \cdot \left( (w - w_S) \wedge n \right) \\ &\quad - \ell_w \cdot \int_{\partial\mathcal{S}_0} D(u^E)n \, ds - r_w \cdot \int_{\partial\mathcal{S}_0} x \wedge D(u^E)n \, ds. \end{aligned}$$

Thus we infer from (89) the following inequality:

$$\begin{aligned} \|w(t, \cdot)\|_{\mathcal{H}}^2 + 4\alpha\nu \int_0^t \int_{\partial\mathcal{S}_0} |w - w_S|^2 + 4\nu \int_0^t \int_{\mathcal{F}_0} |D(w)|^2 \\ \leq \|w_0\|_{\mathcal{H}}^2 - 4\alpha\nu \int_0^t \int_{\partial\mathcal{S}_0} (u^E - u_S^E) \cdot (w - w_S) \\ + 2\nu \int_0^t \int_{\mathcal{F}_0} \Delta u^E \cdot w - 4\nu \int_0^t \int_{\partial\mathcal{S}_0} \left( (D(u^E)n) \wedge n \right) \cdot \left( (w - w_S) \wedge n \right) \\ - 4\nu \int_0^t \ell_w \cdot \int_{\partial\mathcal{S}_0} D(u^E)n \, ds - 4\nu \int_0^t r_w \cdot \int_{\partial\mathcal{S}_0} x \wedge D(u^E)n \, ds - 2 \int_0^t b(w, w, u^E) \\ \leq \|w_0\|_{\mathcal{H}}^2 + \sum_{i=1}^6 I_i. \end{aligned}$$

To deal with  $I_1$  and  $I_3$  we will use the following lemma:

**Lemma 3.** *There exists  $C > 0$  such that for any  $\gamma > 0$  and for any smooth function  $f$  divergence free and tangent to the boundary*

$$\|f\|_{L^2(\partial\mathcal{S}_0)} \leq C\gamma^{1/3}\|f\|_{L^2(\mathcal{F}_0)}^{2/3} + \frac{1}{4\gamma}\|D(f)\|_{L^2(\mathcal{F}_0)}^2 + C\|f\|_{L^2(\mathcal{F}_0)}.$$

*Proof.* We first apply the following standard trace inequality:

$$\|f\|_{L^2(\partial\mathcal{S}_0)} \leq C\|f\|_{L^2(\mathcal{F}_0)}^{1/2}\|f\|_{H^1(\mathcal{F}_0)}^{1/2},$$

then the Korn inequality to find

$$\|f\|_{L^2(\partial\mathcal{S}_0)} \leq C(\|f\|_{L^2(\mathcal{F}_0)}^{1/2}\|D(f)\|_{L^2(\mathcal{F}_0)}^{1/2} + \|f\|_{L^2(\mathcal{F}_0)})$$

and finally Young's inequality to conclude.  $\square$

In order to apply this lemma we are going to substitute to the vector fields  $u_S^E$  and  $w_S$  another divergence free vector field with the same traces on  $\partial\mathcal{S}_0$  but with a better decay at infinity, as we did in Section 3.2. Indeed let  $\chi$  be a smooth cut-off function defined on  $\overline{\mathcal{F}_0}$  such that  $\chi = 1$  in  $\Gamma_c$  and  $\chi = 0$  in  $\mathcal{F}_0 \setminus \Gamma_{2c}$ , where

$$\Gamma_c := \{x \in \mathcal{F}_0 / d(x) < c\} \text{ with } d(x) := \text{dist}(x, \partial\mathcal{S}_0).$$

Let us denote

$$\psi_S^E(t, x) := \frac{1}{2}(\ell^E(t) \wedge x - r^E(t)|x|^2) \text{ and } \tilde{u}_S^E := \text{curl}(\chi\psi_S^E),$$

and let us define similarly  $\tilde{w}_S$ . By Cauchy-Schwarz inequality we obtain

$$I_1 \leq 4\alpha\nu \int_0^t \|u^E - \tilde{u}_S^E\|_{L^2(\partial\mathcal{S}_0)} \|w - \tilde{w}_S\|_{L^2(\partial\mathcal{S}_0)} \leq \alpha\nu C \int_0^t \|w - \tilde{w}_S\|_{L^2(\partial\mathcal{S}_0)}$$

and then applying Lemma 3 with  $\gamma = \frac{\alpha C}{4}$

$$\begin{aligned} I_1 &\leq \nu \int_0^t \|D(w - \tilde{w}_S)\|_{L^2(\mathcal{F}_0)}^2 + \alpha^{4/3}\nu C \int_0^t \|w - \tilde{w}_S\|_{L^2(\mathcal{F}_0)}^{2/3} + \alpha\nu C \int_0^t \|w - \tilde{w}_S\|_{L^2(\mathcal{F}_0)} \\ &\leq \nu \int_0^t \|D(w)\|_{L^2(\mathcal{F}_0)}^2 + \nu C \int_0^t \|w\|_{\mathcal{H}}^2 + \alpha^{4/3}\nu C \int_0^t \|w\|_{\mathcal{H}}^{2/3} + \alpha\nu C \int_0^t \|w\|_{\mathcal{H}}. \end{aligned}$$

Now, thanks again to Cauchy-Schwarz inequality and applying Lemma 3 but this time with  $\gamma = \frac{C}{4}$  we get

$$\begin{aligned} I_3 &\leq 4\nu \int_0^t \|D(u^E)n\|_{L^2(\partial\mathcal{S}_0)} \|w - \tilde{w}_S\|_{L^2(\partial\mathcal{S}_0)} \\ &\leq \nu C \int_0^t \|w - \tilde{w}_S\|_{L^2(\partial\mathcal{S}_0)} \\ &\leq \nu \int_0^t \|D(w)\|_{L^2(\mathcal{F}_0)}^2 + \nu C \int_0^t \|w\|_{\mathcal{H}}^2 + \nu C \int_0^t \|w\|_{\mathcal{H}}^{2/3} + \nu C \int_0^t \|w\|_{\mathcal{H}}. \end{aligned}$$

We simply estimate the following term by

$$I_2 \leq 2\nu \int_0^t \|\Delta u^E\|_{L^2(\mathcal{F}_0)} \|w\|_{L^2(\mathcal{F}_0)} \leq \nu C \int_0^t \|w\|_{L^2(\mathcal{F}_0)}.$$

Finally it is straightforward that we can estimate the last terms by

$$I_4 + I_5 \leq \nu C \int_0^t \|w\|_{\mathcal{H}} \text{ and } I_6 \leq C \int_0^t \|w\|_{\mathcal{H}}^2$$

thanks to (42).

We deduce from the above relations that

$$\|w(t)\|_{\mathcal{H}}^2 + 2\nu \int_0^t \|D(w)\|_{L^2(\mathcal{F}_0)}^2 \leq \beta(t) + C \int_0^t \|w\|_{\mathcal{H}}^2,$$

with

$$\beta(t) := \|w_0\|_{\mathcal{H}}^2 + \nu C \int_0^t \|w\|_{\mathcal{H}}^2 + (1 + \alpha^{4/3})\nu C \int_0^t \|w\|_{\mathcal{H}}^{2/3} + (1 + \alpha)\nu C \int_0^t \|w\|_{\mathcal{H}}.$$

Since  $\|w(t)\|_{\mathcal{H}} \leq C$  we can deduce that

$$\beta(t) \leq \|w_0\|_{\mathcal{H}}^2 + (1 + \alpha + \alpha^{4/3})\nu t C \|w\|_{L^\infty(0,T;\mathcal{H})}^{2/3},$$

and finally, the Gronwall Lemma implies that

$$\begin{aligned} \|w(t)\|_{\mathcal{H}}^2 &\leq \|w_0\|_{\mathcal{H}}^2 + (1 + \alpha + \alpha^{4/3})\nu t C \|w\|_{L^\infty(0,T;\mathcal{H})}^{2/3} \\ &\quad + C \int_0^t \left( \|w_0\|_{\mathcal{H}}^2 + s(1 + \alpha + \alpha^{4/3})\nu C \|w\|_{L^\infty(0,T;\mathcal{H})}^{2/3} \right) ds \exp(Ct) \\ &\leq C \left( \|w_0\|_{\mathcal{H}}^2 + (1 + \alpha + \alpha^{4/3})\nu \|w\|_{L^\infty(0,T;\mathcal{H})}^{2/3} \right), \end{aligned}$$

where  $C$  is a constant depending on  $T$ .

By setting  $u_0 = u_0^E$ , we obtain estimate (88).

The proof of Theorem 5 is then complete.

**Acknowledgements.** This work was partially supported by the CNRS-FAPESP cooperation. The first author thanks the Laboratoire Jacques-Louis Lions - Paris 6, while the second author thanks the IMECC-UNICAMP for their kind hospitality during their visits there. The first author was partially supported by CNPq-Brazil, grant 303302/2009-7 and by FAPESP-Brazil, grant 2007/51490-7. The second author was partially supported by the Agence Nationale de la Recherche, Project CISIFS, grant ANR-09-BLAN-0213-02. He also thanks Olivier Glass and David Gérard-Varet for some fruitful discussions.

## References

- [1] C. Bardos, F. Golse, L. Paillard. *The incompressible Euler limit of the Boltzmann equation with accommodation boundary condition*. Commun. Math. Sci. 10 (2012), no. 1, 159-190.
- [2] C. Bardos, E. S. Titi. *Euler equations for an ideal incompressible fluid*. (Russian) Uspekhi Mat. Nauk 62 (2007), no. 3(375), 5-46; translation in Russian Math. Surveys 62 (2007), no. 3, 409-451.
- [3] H. Beirao da Veiga, F. Crispo. *A missed persistence property for the Euler equations, and its effect on inviscid limits*. Nonlinearity 25 (2012) 1661-1669.
- [4] T. Chambrion, A. Munnier. *Locomotion and control of a self-propelled shape-changing body in a fluid*. J. Nonlinear Sci. 21 (2011), no. 3, 325-385.
- [5] M. Chapouly. *On the global null controllability of a Navier-Stokes system with Navier slip boundary conditions*. J. Differential Equations 247 (2009), no. 7, 2094-2123.
- [6] S. Childress. *An introduction to theoretical fluid mechanics*. Courant Lecture Notes in Mathematics, 19. Courant Institute of Mathematical Sciences, New York; American Mathematical Society, Providence, RI, 2009.
- [7] T. Clopeau, A. Mikelić, R. Robert. *On the vanishing viscosity limit for the 2D incompressible Navier-Stokes equations with the friction type boundary conditions*. Nonlinearity 11 (1998), no. 6, 1625-1636.

- [8] C. Conca, J. A. San Martin, M. Tucsnak. *Existence of solutions for the equations modelling the motion of a rigid body in a viscous fluid*. Comm. Partial Differential Equations 25 (2000), no. 5-6, 1019-1042.
- [9] P. Constantin. *On the Euler equations of incompressible fluids*. Bull. Amer. Math. Soc. (N.S.) 44 (2007), no. 4, 603-621.
- [10] F. Coron. *Derivation of slip boundary conditions for the Navier-Stokes system from the Boltzmann equation*. J. Statist. Phys. 54 (1989), no. 3-4, 829-857.
- [11] J.-M. Coron. *On the controllability of the 2-D incompressible Navier-Stokes equations with the Navier slip boundary conditions*. ESAIM Control Optim. Calc. Var. 1 (1995/96), 35-75.
- [12] J.-M. Coron. *On the null asymptotic stabilization of the two-dimensional incompressible Euler equations in a simply connected domain*. SIAM J. Control Optim. 37 (1999), no. 6, 1874-1896.
- [13] A.-L. Dalibard, D. Gérard-Varet. *Effective boundary condition at a rough surface starting from a slip condition*. J. Differential Equations 251 (2011), no. 12, 3450-3487.
- [14] B. Desjardins, M. J. Esteban. *On weak solutions for fluid-rigid structure interaction: compressible and incompressible models*. Comm. Partial Differential Equations 25 (2000), no. 7-8, 1399-1413.
- [15] B. Desjardins, M. J. Esteban. *Existence of weak solutions for the motion of rigid bodies in a viscous fluid*. Arch. Ration. Mech. Anal. 146 (1999), no. 1, 59-71.
- [16] W. E. *Boundary layer theory and the zero-viscosity limit of the Navier-Stokes equation*. Acta Math. Sin. (Engl. Ser.) 16 (2000), no. 2, 207-218.
- [17] G. P. Galdi. *An Introduction to the Mathematical Theory of the Navier-Stokes Equations*, Vol. I, Springer, New York, 1994.
- [18] D. Gérard-Varet, E. Dormy. *On the ill-posedness of the Prandtl equation*. J. Amer. Math. Soc. 23 (2010), no. 2, 591-609.
- [19] D. Gérard-Varet, N. Masmoudi. *Relevance of the slip condition for fluid flows near an irregular boundary*. Comm. Math. Phys. 295 (2010), no. 1, 99-137.
- [20] P. Gamblin, X. Saint Raymond. *On three-dimensional vortex patches*. Bull. Soc. Math. France 123 (1995), no. 3, 375-424.
- [21] O. Glass, F. Sueur. *Uniqueness results for weak solutions of two-dimensional fluid-solid systems*. Preprint 2012, [arXiv:1203.2894](https://arxiv.org/abs/1203.2894).
- [22] O. Glass, F. Sueur, T. Takahashi. *Smoothness of the motion of a rigid body immersed in an incompressible perfect fluid*. Ann. Sci. École Norm. Sup. 45 (2012), no. 1, 1-51.
- [23] E. Grenier. *Boundary layers*. Handbook of mathematical fluid dynamics. Vol. III, 245-309, 2004.
- [24] Y. Guo, T. T. Nguyen. *A note on the Prandtl boundary layers*. Comm. Pure Appl. Math. 64 (2011), no. 10, 1416-1438.
- [25] J.-G. Houot, J. San Martin and M. Tucsnak. *Existence and uniqueness of solutions for the equations modelling the motion of rigid bodies in a perfect fluid*. J. Funct. Anal. 259 (2010), no. 11, 2856-2885.
- [26] D. Iftimie, G. Planas. *Inviscid limits for the Navier-Stokes equations with Navier friction boundary conditions*. Nonlinearity 19 (2006), 899-918.
- [27] D. Iftimie, F. Sueur. *Viscous boundary layers for the Navier-Stokes equations with the Navier slip conditions*. Arch. Ration. Mech. Analysis 199 (2011), no. 1, 145-175.
- [28] T. Kato. *Remarks on zero viscosity limit for nonstationary Navier-Stokes flows with boundary*. Seminar on nonlinear partial differential equations, 85-98, Math. Sci. Res. Inst. Publ., 2, 1984.

- [29] N. Masmoudi, F. Rousset. *Uniform regularity for the Navier-Stokes equations with Navier boundary condition.* Arch. Ration. Mech. Analysis 203 (2012), no. 2, 529-575.
- [30] N. Masmoudi, L. Saint-Raymond. *From the Boltzmann equation to the Stokes-Fourier system in a bounded domain.* Comm. Pure Appl. Math. 56 (2003), no. 9, 1263-1293.
- [31] C-L. Navier. *Mémoire sur les lois du mouvement des fluides.* Mem. Acad. R. Sci. Paris. 6 (1823), 389-416.
- [32] J. H. Ortega, L. Rosier, T. Takahashi. *Classical solutions for the equations modelling the motion of a ball in a bidimensional incompressible perfect fluid.* M2AN Math. Model. Numer. Anal. 39 (2005), no. 1, 79-108.
- [33] J. H. Ortega, L. Rosier, T. Takahashi. *On the motion of a rigid body immersed in a bidimensional incompressible perfect fluid,* Ann. Inst. H. Poincaré Anal. Non Linéaire 24 (2007), no. 1, 139-165.
- [34] M. Paddick. *Stability and instability of Navier boundary layers.* Preprint 2011, [arXiv:1103.5009](https://arxiv.org/abs/1103.5009).
- [35] C. Rosier, L. Rosier. *Smooth solutions for the motion of a ball in an incompressible perfect fluid,* J. Funct. Anal. 256 (2009), no. 5, 1618-1641.
- [36] J. A. San Martin, V. Starovoitov, M. Tucsnak. *Global weak solutions for the two-dimensional motion of several rigid bodies in an incompressible viscous fluid.* Arch. Ration. Mech. Anal. 161 (2002), no. 2, 113-147.
- [37] D. Serre. *Chute libre d'un solide dans un fluide visqueux incompressible. Existence.* Japan J. Appl. Math. 4 (1987), no. 1, 99-110.
- [38] F. Sueur. *A Kato type Theorem for the inviscid limit of the Navier-Stokes equations with a moving rigid body.* To appear in Comm. Math. Phys.
- [39] R. Temam. *Problèmes mathématiques en plasticité.* Méthodes Mathématiques de l'Informatique, 12. Gauthier-Villars, 1983.
- [40] R. Temam. *Navier-Stokes equations and nonlinear functional analysis. Second edition.* CBMS-NSF Regional Conference Series in Applied Mathematics 66, 1995.
- [41] L. Wang, Z. Xin, A. Zang. *Vanishing viscous limits for 3D Navier-Stokes equations with Navier-slip boundary conditions.* Preprint 2012, [arXiv:1201.1986v2](https://arxiv.org/abs/1201.1986v2).
- [42] Y. Wang, A. Zang. *Smooth solutions for motion of a rigid body of general form in an incompressible perfect fluid.* J. Differential Equations, 252 (2012), 4259-4288.